

**February 1, 2017  
DRAFT**

**(FINAL DRAFT FOR REVIEW  
AND ADOPTION)**

**Sent to NYSDEC & NYCDEP on  
6-30-15 for approval prior to SEQR  
Review and Adoption Process**

**CITY OF PORT JERVIS  
SEWER USE LAW**

**Submitted by:**

**Carole L. Gallagher, Esq.**

**Gallagher & Gallagher  
225 Route 284  
P.O. Box 333  
Unionville, NY 10988**

**Tel: (845) 726-4657  
gallagherlaw@optimum.net**

### General Table Of Contents

Article	Title
1	Short Title and Purpose
2	Definitions
3	Use of Public Sewers Required
4	Private Wastewater Disposal
5	New Sewers or Sewer Extensions
6	Building Laterals, Street Laterals, Connections, and Fees
7	Inflow
8	Reserved
9	Discharge Restrictions
10	Discharge Permits and Pretreatment Requirements
11	Enforcement and Penalties
12	Charges
13	Public Disclosure of POTW Operation
14	Conflicts, Severability, Effective Date and Applicability
Appendix	Table of Parameters of Concern

## **Specific Table of Contents**

### **Article 1 - Short Title and Purpose**

- Section 101 - Short Title
- Section 102 - General Purpose
- Section 103 - Specific Purposes
- Section 104 - Replacement of Previous Sewer Use Law

### **Article 2 - Definitions**

- Section 201 - Defined Terms
- Section 202 - Abbreviations
- Section 203 - Undefined Terms

### **Article 3 - Use of Public Sewers Required**

- Section 301 - Waste Disposal Unlawful
- Section 302 - Connecting Private Sewage System to Storm Sewer Unlawful
- Section 303 - Discharge of Sewage into Well Prohibited
- Section 304 - Wastewater Discharge Unlawful
- Section 305 - Building Permit Allowed Only When Approved Wastewater Disposal Available
- Section 306 - Private Wastewater Disposal Unlawful
- Section 307 - Connection to Public Sewer Required
- Section 308 - Limitation on Use of Public Sewers
- Section 309 - Reserved
- Section 310 - Moratorium
- Section 311 - Basis of Sewer Use Requirement
- Section 312 - Exceptions to Connection to Public Sewer

### **Article 4 - Private Wastewater Disposal**

- Section 401 - Public Sewer Unavailable - Private Wastewater Disposal Required
- Section 402 - Connection of Two Buildings to the Same Septic Tank Prohibited
- Section 403 - Construction Permit Application
- Section 404 - Construction Permit
- Section 405 - Preventing Nuisances - Rehabilitation Required
- Section 406 - Sanitary Operation Required
- Section 407 - Septage Removal
- Section 408 - Direct Connection to New Public Sewers Required
- Section 409 - Additional Requirements

### **Article 5 - New Sewers or Sewer Extensions**

Section 501 - Proper Design  
Section 502A - New Sewers Subject to Approval, Fees, Inspection, Testing, and Reporting  
Section 502B - Plans, Specification, and Pipe Test Results Required  
Section 503A - Gravity Sewer Pipe  
Section 503B - Safety and Load Factors  
Section 503C - Sewer Pipe Installation  
Section 503D - Cleanout Installation  
Section 504 - Manholes and Manhole Installation  
Section 505A - Low Pressure Air Testing  
Section 505B - Test Section  
Section 505C - Pipe Lamping  
Section 505D - Deflection Testing  
Section 505E - Vacuum Testing  
Section 506A - Force Mains  
Section 506B - Force Main Testing  
Section 507 - Final Acceptance and Warranty/Surety  
Section 508 - Liability Insurance Coverage During Construction Period

#### **Article 6 - Building Laterals, Street Laterals, Connections, and Fees**

Section 601A - Permit Required for Sewer Connections  
Section 601B - Inflow/Infiltration Prohibited  
Section 602 - Sewer Lateral Permits  
Section 603A - New Building Laterals  
Section 603B - Laterals Serving Several Buildings  
Section 603C - Laterals Serving Complexes  
Section 603D - Dry Sewers  
Section 604 - Using Existing Building Laterals  
Section 605 - Lateral Pipe Materials  
Section 606A - Street Lateral to Public Sewer Connection  
Section 606B - Future Connection Locations; As-Built Drawings  
Section 606C - Special Manhole Requirements  
Section 607 - Laterals At and Near Buildings  
Section 608 - Sewage Lifting  
Section 609 - Lateral Pipe Installation  
Section 610A - Watertight Joints  
Section 610B - Cast Iron Push Joints  
Section 610C - PVC Push Joints  
Section 611A - Building Lateral/Street Lateral Connection  
Section 611B - Cleanout Repair/Replacement  
Section 611C - Street Lateral Replacement; Ownership  
Section 612 - Testing  
Section 613A - Connection Inspection  
Section 613B - Trench Inspections  
Section 614 - Public Safety Provisions Required; Restoration of Disturbed Areas

Section 615 - Interior Clean-Out  
Section 616 - Costs Borne by Owner

### **Article 7 - Inflow**

Section 701 - New Inflow Sources Prohibited  
Section 702 - Existing Inflow Sources Disconnected  
Section 703 - Existing Inflow Sources Disconnected When Property Sold  
Section 704 - No Re-connection of Inflow Source Allowed  
Section 705 - Charges for Inflow

### **Article 8 – Reserved**

### **Article 9 - Discharge Restrictions**

Section 901 - Pretreatment Standards  
Section 902 - General Prohibitions  
Section 903 - Concentration Based Limitations  
Section 904 - Mass Discharge Based Limitations  
Section 905 - Modification of Limitations  
Section 906 - Access to User's Records  
Section 907 - Dilution  
Section 908 - Grease, Oil, and Sand Interceptors  
Section 909 - Solid Waste Grinders  
Section 910 - Rejection of Wastewater

### **Article 10 - Discharge Permits and Pretreatment Requirements**

Section 1001 - Wastewater Discharge Reports  
Section 1002 - Notification to Industrial Users  
Section 1003A - Wastewater Discharges  
Section 1003B - Wastewater Discharge Permits Required For Significant Industrial Users  
Section 1003C - Other Industrial Users  
Section 1003D - Discharge Permits to Storm Sewers Not Authorized  
Section 1004A - Application for Wastewater Discharge Permits  
Section 1004B - Permit Modifications  
Section 1004C - Permit Conditions  
Section 1004D - Permit Duration  
Section 1004E - Permit Reissuance  
Section 1004F - Permit Transfer  
Section 1004G - Permit Revocation  
Section 1004H - Reserved  
Section 1005 - Reporting Requirements for Permittee  
Section 1006 - Flow Equalization  
Section 1007 - Monitoring Stations (Control Manholes)

Section 1008 - Proper Design and Maintenance of Facilities and Monitoring Stations  
Section 1009 - Vandalism, Tampering with Measuring Devices  
Section 1010 - Sampling and Analysis  
Section 1011 - Accidental Discharges; SPCC Plan  
Section 1012 - Posting Notices  
Section 1013 - Sample Splitting  
Section 1014 - Public Access to Information Maintained by the Director  
Section 1015A - Access to Property and Records  
Section 1015B - Access to Easements  
Section 1015C - Liability of Property Owner  
Section 1016 - Special Agreements

## **Article 11 - Enforcement and Penalties**

Section 1101 - Enforcement Response Plan

### Administrative Remedies

Section 1102 - Notification of Violation  
Section 1103 - Consent Orders  
Section 1104 - Administrative or Compliance Orders  
Section 1105 - Administrative Fines  
Section 1106 - Cease and Desist Orders  
Section 1107 - Termination of Permit  
Section 1108 - Water Supply Severance  
Section 1109 - Show Cause Hearing  
Section 1110 - Failure of User to Petition the Director  
Section 1111 - Notice  
Section 1112 - Right to Choose Multiple Remedies

### Judicial Remedies

Section 1113 - Civil Actions for Penalties  
Section 1114 - Court Orders  
Section 1115 - Criminal Penalties  
Section 1116 - Injunctive Relief  
Section 1117 - Summary Abatement

### Miscellaneous

Section 1118 - Delinquent Payments  
Section 1119 - Performance Bonds  
Section 1120 - Liability Insurance  
Section 1121 - Informant Rewards

## **Article 12 - Charges**

Section 1201 - Normal Sewage Service Charges  
Section 1202 - Surcharge for Abnormal Sewage  
Section 1203 - Total Sewer Service Charge  
Section 1204 - Segmenting the POTW  
Section 1205 - Measurement of Flow  
Section 1206 - Billing Period  
Section 1207 - Pretreatment Program Costs  
Section 1208 - Reserved  
Section 1209 - Capital Recovery  
Section 1210 - Collection of Charges  
Section 1211 - Fiscal Year for System  
Section 1212 - Impact Fees  
Section 1213 - Use of Revenues  
Section 1214 - Records and Accounts

### **Article 13 - Public Disclosure of POTW Operations**

Section 1301 - POTW Operations Open to the Public  
Section 1302 - Procedural Requirements Available  
Section 1303 - Validity Through Public Inspection

### **Article 14 - Conflicts, Severability, Effective Date and Applicability**

Section 1401 - Conflicts  
Section 1402 - Severability  
Section 1403 - Effective Date  
Section 1404 - Applicability

### **Appendix - Parameters of Concern**

Class A - Halogenated Hydrocarbons  
Class B - Halogenated Organics (Other than Hydrocarbons)  
Class C - Pesticides (Includes Herbicides, Algaecides, Biocides, Slimicides and Mildewcides)  
Class D - Aromatic Hydrocarbons  
Class E - Tars  
Class F - Aromatics (Other than Hydrocarbons and Non-Halogenated)  
Class G - Miscellaneous  
Class M - Metals and their Compounds

### **Article 1**

#### **Short Title and Purpose**

Section 101 - Short Title  
Section 102 - General Purpose  
Section 103 - Specific Purposes  
Section 104 - Replacement of Previous Sewer Use Law

**Section 101 - Short Title** For brevity and ease of communication, this Law may be cited as the City of Port Jervis Sewer Use Law.

**Section 102 - General Purpose** The general purpose of this Law is the following:

To provide for efficient, economic, environmentally safe, and legal operation of the City of Port Jervis POTW (also referred to herein as the POTW).

**Section 103 - Specific Purposes** The specific purposes of this Law are the following:

(1) To prevent the introduction of substances into the POTW that will:

1. interfere with the POTW in any way,
2. pass through the POTW to the State's waters and cause contravention of standards for those waters or cause violation of the POTW's SPDES permit,
3. increase the cost or otherwise hamper the disposal of POTW sludge and/or residuals,
4. endanger municipal and/or POTW employees or contractors,
5. cause air pollution, or groundwater pollution, directly or indirectly,
6. cause, directly or indirectly, any public nuisance condition.

(2) To prevent new sources of infiltration and inflow and, as much as possible, eliminate existing sources of infiltration and inflow.

(3) To assure that new sewers and connections are properly constructed.

**Section 104 - Replacement of Previous Sewer Use Law** The provisions in the existing City Of Port Jervis Code entitled "Ordinance Regulating Sewers and Sewage Disposal of 1968" are hereby repealed and said provisions are replaced by the herein set forth Articles 1 through 14 inclusive

## **Article 2**

### **Definitions**

Section 201 - Defined Terms

Section 202 - Abbreviations

Section 203 - Undefined Terms

**Section 201 - Defined Terms** Unless otherwise stated in the section where the term is used in this Law, the meaning of terms used in this Law shall be as stated below. When not inconsistent with the context, the present tense shall include the future, and words used in the plural shall include the



singular and vice versa. Furthermore, a masculine pronoun shall include the feminine. Shall is mandatory; may is permissive.

**Abnormal Sewage** - Sewage whose concentration of one or more characteristics of normal sewage exceeds the maximum concentrations of the characteristics of normal sewage. See normal sewage.

**Act or "THE ACT"** - The Federal Water Pollution Control Act, also known as the Clean Water Act, as amended, 33 U.S.C. 1251, et seq., as may be amended.

**Administrator** - The Regional Administrator of the U. S. Environmental Protection Agency (USEPA), Region 2.

**Ammonia** - The result obtained, using an approved laboratory procedure, to determine the quantity of ammonia in a sample, expressed as milligrams of nitrogen per liter.

**Applicant** - That person who makes application for any permit. The Applicant may be an owner, new or old, or his agent.

**Approval Authority** - The USEPA, or the New York State Department of Environmental Conservation (NYSDEC), in the event the NYSDEC is delegated approval authority responsibility by the USEPA.

**Approved Laboratory Procedure** - The procedures defined as 'Standard Methods' in this article, or other procedures approved by the Director, for flow measurement or determination of the concentration of pollutants or their surrogates in waters, wastewaters, and/or sludges.

**ASTM, denoting American Society for Testing and Materials** - The latest edition of any ASTM specification, when stipulated in this Law.

**Authorized Representative of the Industrial User** - An authorized representative of the industrial user may be: a) A principal executive officer of at least the level of vice-president, if the industrial user is a corporation; (b) A general partner or proprietor, if the industrial user is a partnership or proprietorship, respectively; (c) A duly authorized representative of the individual designated above, if such representative is responsible for the overall operation of the facilities from which the indirect discharge originates.

**BOD, denoting Biochemical Oxygen Demand** - The result obtained when using an approved laboratory procedure to determine the quantity of oxygen utilized in the aerobic biochemical oxidation of organic matter or in a sample, expressed in milligrams per liter.

**Builder** - Any person who undertakes to construct a building or any part of a building, either under contract or for resale.

**Building Drain** - That part of the lowest horizontal piping of a building drainage system that receives the discharge from soil, waste, and other drainage pipes inside the building walls, and conveys it to the building lateral, which begins five (5) feet outside the inner face of the building wall.

**Building Official**- That individual nominated by the City of Port Jervis Mayor and confirmed by the City of Port Jervis Common Council as the Building Official to administer the City's Building Department. Such an individual has the knowledge and the authority to inspect and make determinations for the City of Port Jervis regarding the construction of, safety of, suitability for habitation or suitability for other uses, of all types of buildings and other structures that are located within the City of Port Jervis. At certain times, as provided for in this Law and in the City's Building Codes, the Building Official's authority and opinion will be required in relation to sewage connections or other structures or facilities which are located at or in a building or structure. This definition shall also include the Building Official's authorized deputy, agent, or representative.

**Chlorine Demand** - The result obtained when using an approved laboratory procedure to determine the difference between the amount of chlorine added to a sample and the amount of chlorine remaining in the sample at the end of a specified contact time at room temperature, expressed in milligrams per liter.

**City** - The City of Port Jervis, incorporated in 1907.

**COD, denoting Chemical Oxygen Demand** - The result obtained when using an approved laboratory procedure to measure the oxygen requirement of that portion of matter, in a sample, that is susceptible to oxidation, by a specific chemical oxidant, expressed in milligrams per liter.

**Color** - The optical density at the visual wave length of maximum absorption, relative to distilled water. One hundred percent (100%) transmittance is equivalent to zero (0.0) optical density.

**Composite Sample** - The sample resulting from the combination of individual samples of wastewater taken at selected intervals, for a specified time period. The individual samples may have equal volumes or the individual volumes may be proportioned to the flow at the time of sampling.

**Connection** - Attachment of one user to a sewer. (See Extension)

**Connection Charge (Tap Fee)** - The one time application fee to offset City of Port Jervis expenses to process an application for a connection of a building/street lateral to the public sewer. The fee also covers plan review,

permit issuance, street repair cost, and inspection costs. The fee may be scaled to the amount of work involved, or to the size of the public sewer involved.

**Control Authority** - The term shall refer to "Approval Authority," or to the Director of Public Works when City Of Port Jervis has an approved pretreatment program under the provisions of 40 CFR 403.11.

**Control Manhole** - A manhole accessible to the Control Authority in or upstream of the street lateral, such that samples collected from the manhole represent the discharge to the POTW.

**Conventional Pollutant** - A pollutant that the POTW treatment plant was designed to treat, defined in accordance with the Act.

**Cooling Water** - The water discharged from any system of condensation, air conditioning, refrigeration, or other sources. It shall contain no polluting substances which would produce COD or suspended solids in excess of five (5) milligrams per liter, or toxic substances, as limited elsewhere in this Law.

**County** - Orange County, New York.

**DEP - The New York City Department of Environmental Protection** - which owns and operates the POTW Treatment Plant pursuant to the 1954 U.S. Supreme Court Decree, 347 U.S. 995 (1954).

**Developer** - Any person who subdivides land for the purpose of constructing, or causing to be constructed, buildings for which wastewater disposal facilities are required.

**Direct Discharge** - The discharge of treated or untreated wastewater directly to the Waters of the State of New York. (For reference, see Indirect Discharge.)

**Director of Public Works or Director-** That individual nominated by the City of Port Jervis Mayor and confirmed by the City of Port Jervis Common Council as the Director of Public Works of Water and Wastewater. Such an individual shall be qualified to oversee wastewater collection, treatment and distribution and POTW collection system operations. This definition shall also include his authorized deputy, agents, or representatives.

**Domestic Wastes** - see Sewage, Domestic.

**Dry Sewer** - The sanitary sewer installed in anticipation of future connection to a POTW but which is not used, in the meantime, for transport of storm or sanitary sewage.

**End of Pipe** - For the purpose of determining compliance with limitations prescribed by Article 9, end of pipe shall mean the control manhole, provided the samples collected from the control manhole are representative of the discharge to the POTW.

**End of Pipe Concentration** - The concentration of a substance in a sample of wastewater at end of pipe.

**End of Process Concentration** - see National Categorical Pretreatment Standard.

**Easement** - An acquired legal right for the specific use of land owned by others.

**EPA, USEPA, or U.S. Environmental Protection Agency** - The agency of the federal government charged with the administration and enforcement of federal environmental laws, rules, and regulations. Also may be used as a designation for the Administrator or other duly authorized official of this Agency.

**Extension** - Attachment to a sewer line, with more than one user, to an existing sewer line.

**Facility** - All buildings, other structures, grounds and contiguous property at any locations related to or connected with a user at the user's location.

**Floatable Oil** - Oil, grease, or fat in a physical state such that it will separate by gravity from wastewater by treatment in a wastewater treatment facility.

**Flow Rate** - The quantity of liquid or waste that flows in a certain period of time.

**Garbage** - The solid wastes from the preparation, cooking, and dispensing of food, from the handling, storage, and sale of produce, and from the packaging and canning of food.

**Grab Sample** - A single sample of wastewater representing the physical, chemical, and biological characteristics of the wastewater at one point and time.

**ICS Form** - The form used by the NYSDEC to survey industries to perform and update the Industrial Chemical Survey.

**Indirect Discharge** - The introduction of wastewater into a POTW for treatment and ultimate discharge of the treated effluent to the State's Waters. (For reference, see Direct Discharge).

**Industrial** - Meaning or pertaining to industry, manufacturing, commerce, trade, business, or institution, and is distinguished from domestic or residential.

**Industrial Chemical Survey (ICS)** - The survey of industries in New York State, initiated by the NYSDEC, to determine chemical usage and storage by those industries.

**Industrial User** - See User, Industrial.

**Industrial Wastes** - The liquid or liquid-carried solid, liquid and/or gaseous wastes from industrial manufacturing processes, trade, service, utility, or business, as distinct from sanitary sewage.

**Infiltration** - Water, other than wastewater, that enters a sewer system (excluding building drains) from the ground through such means as defective pipes, pipe joints, connections, or manholes. Infiltration does not include, and is distinguished from, inflow. Infiltration is inadvertent, that is, not purposely designed or built into the sewer or drain.

**Inflow** - Water, other than wastewater, that enters a sewer system (including building drains) from sources such as, but not limited to, roof leaders, cellar drains, area drains, drains from springs and swampy areas, manhole covers, cross connections between storm sewers and sanitary sewers, catch basins, cooling towers, storm waters, foundation drains, swimming pools, surface runoff, street wash waters, or drainage. Inflow does not include, and is distinguished from, infiltration. Inflow is purposely designed and/or built into the sewer or drain.

**Interference** - A discharge which, alone or in conjunction with discharges by other sources,

(a) inhibits or disrupts the POTW, its treatment processes or operations, or its sludge processes, use or disposal; and

(b) therefore is a cause of a violation of any requirement of the POTW's SPDES permit (including an increase in the magnitude or duration of a violation) or of the prevention of sewage sludge use or disposal by the POTW in accordance with the following statutory provisions and regulations or permits issued thereunder (or more stringent State or local regulations):

- i - Section 405 of the Clean Water Act,
- ii - the Solid Waste Disposal Act (SWDA) (including Title II, more commonly referred to as the Resource Conservation and Recovery Act - RCRA), and including State regulations contained in any State sludge management plan prepared pursuant to Subtitle D of the SWDA),
- iii - Clean Air Act

iv - Toxic Substance Control Act, and  
v - Marine Protection Research and Sanctuaries Act.

**Lateral, Building** - The sewer extension from the building drain to the Street Lateral or other place of wastewater disposal.

**Lateral, Street** - The sewer extension from the public sewer to the property line.

**National Categorical Pretreatment Standard, or Categorical Standard** - Any regulation containing pollutant discharge limits promulgated by the EPA in accordance with Section 307 (B) and (C) of the Act (22 U.S.C. 1347), which applies to a specific category of industrial users. These standards apply at the end of the categorical process ("end of process").

**National Pollutant Discharge Elimination System (NPDES) Permit** - A permit issued pursuant to Section 402 of the Act (33 U.S.C. 1342).

**National Prohibitive Discharge Standard, or Prohibitive Discharge Standard** - Any regulation developed under the authority of Section 307 (B) of the Act, and 40 CFR, Section 403.5.

**Natural Outlet** - Any outlet, including storm sewers and combined sewer overflows, to State's Waters.

**New Owner** - That individual or entity who purchased property within the Service Area of the City of Port Jervis after the effective date of this law.

**New Source** - Any source, the construction of which is commenced after the publication of the proposed regulation prescribing a Section 307 (C) (33 U.S.C 1317) Categorical Pretreatment Standard which will be applicable to such source, if such standard is thereafter promulgated.

**New User** - A discharger to the POTW who commences discharge after the effective date of this Law.

**Normal Sewage** - see Sewage, Normal.

**Nuisance** - The use or lack of use of the POTW in such a manner so as to endanger life or health, give offense to the senses, or obstruct or otherwise interfere with the reasonable use or maintenance of the POTW.

**Oil and Grease** - The result obtained when using an approved laboratory procedure to determine the quantity of fats, wax, grease, and oil, in a sample, expressed in milligrams per liter.

**Old Owner** - That individual or entity who owns or owned a property, within the Service Area of the POTW, purchased prior to the effective date of this Law, who or inherited the property at any time and intends to sell the property, or has sold the property to a new owner, also the agent of the old owner.

**Other Wastes** - Garbage (shredded or unshredded), refuse, wood, egg shells, coffee grounds, sawdust, shavings, bark, sand, lime, ashes, and all other discarded matter not normally present in sewage or industrial wastes. Also, the discarded matter not normally present in sewage or industrial waste.

**Pass Through** - The discharge which exits the POTW into waters of the State in quantities, which, alone or in conjunction with Discharges from other sources, is a cause of a violation of any requirement of the POTW's SPDES permit (including an increase in the magnitude or duration of a violation).

**Permit** - A temporary revocable written document allowing use of the POTW for specified wastes over a limited period of time, containing sampling locations and reporting frequencies, and requiring other actions as authorized by this Law.

**Person** - Any individual, public or private corporation, political subdivision, Federal, State, or local agency or entity, association, trust, estate or any other legal entity whatsoever.

**pH** - The logarithm (base 10) of the reciprocal of the weight of hydrogen ions, in gram moles per liter of solution. A pH value of 7.0, the pH scale mid point, represents neutrality. Values above 7.0 represent alkaline conditions. Values below 7.0 represent acid conditions.

**Phosphorus, total** - See total phosphorus.

**Pollutant** - Any material placed into or onto the State's waters, lands and/or airs, which interferes with the beneficial use of that water, land and/or air by any living thing at any time.

**Pollution** - The man-made or man-induced alteration of the chemical, physical, biological, and/or radiological integrity of the State's waters, lands and/or airs resulting from the introduction of a pollutant into these media.

**POTW Collection System or POTWCS** - That portion of the City of Port Jervis POTW that is owned and operated or maintained by the City of Port Jervis which collects and conveys sewage to the POTW Treatment Plant.

**POTW Treatment Plant** - That portion of the POTW that is owned by the City of New York and operated by the New York City Department of

Environmental Protection that provides treatment to wastewater and treats sludge and residuals derived from such treatment and the pump stations partly treating and conveying that wastewater.

**Pretreatment (Treatment)** - The reduction of the amount of pollutants, the elimination of pollutants, or the alteration of the nature of pollutant properties in wastewater to a less harmful state prior to or in lieu of discharging or otherwise introducing such pollutants into a POTW. The reduction or alteration can be achieved by physical, chemical, or biological process, process changes, or by other means, except as prohibited by 40 CFR, Section 403.6 (D).

**Pretreatment Requirements** - Any substantive or procedural requirement related to pretreatment, other than a National Pretreatment Standard imposed on an industrial user.

**Pretreatment Standard or National Pretreatment Standard** -Any Categorical Standard or Prohibitive Discharge Standard.

**Priority Pollutants** - The most recently revised or updated list, developed by the EPA, in accordance with the Act.

**Prohibitive Discharge Standard** - see National Prohibitive Discharge Standard.

**Properly Shredded Garbage** - The wastes from the preparation, cooking, and dispensing of food that have been shredded to such a degree that all particles will be carried freely under the flow conditions normally prevailing in public sewers, and with no particle having a dimension greater than one-half (1/2) inch in any dimension.

**Publicly Owned Treatment Works (POTW)** - The treatment works, as defined by Section 212 of the Act, (33 U.S.C 1292) that services the City of Port Jervis. This definition includes any sewers and appurtenances that transport wastewater to the POTW Treatment Plant, but does not include pipes, sewers, or other conveyances not connected directly or indirectly to a facility providing treatment.

**Receiving Waters** - A natural watercourse or body of water (usually Waters of the State) into which treated or untreated sewage is discharged.

**Records** - Shall include, but not be limited to, any printed, typewritten, handwritten or otherwise recorded matter of whatever character (including paper or electronic media), including but not limited to, letters, files, memoranda, directives, notes and notebooks, correspondence, descriptions, telephone call slips, photographs, permits, applications, reports, compilations, films, graphs and inspection reports. For the purposes of this



law, records shall mean records of and relating to waste generation, reuse and disposal, and shall include records of usage of raw materials.

**Roof Drain** - A drain installed to receive water collecting on the surface of a roof for disposal.

**Septage** - All liquids and solids in and removed from septic tanks, holding tanks, cesspools, or approved type of chemical toilets, including but not limited to those serving private residences, commercial establishments, institutions, and industries. Also sludge from small sewage treatment plants. Septage shall not have been contaminated with substances of concern or priority pollutants.

**Septic Tank** - A private domestic sewage treatment system consisting of an underground tank (with suitable baffling), constructed and installed in accordance with any and/or all local and State requirements.

**Service Area of the POTW** - The legally defined bounds of real property from which wastewater may be discharged into the POTW. The bounds shall be established, altered, changed, modified, reduced, enlarged, combined, or consolidated by action of the City of Port Jervis Common Council.

**Sewage** - A combination of the water-carried wastes from residences, business buildings, institutions, and industrial establishments, and such ground, surface, and storm water as may be inadvertently present. The admixture of sewage, as defined above, with industrial wastes and other wastes shall also be considered "sewage", within the meaning of this definition.

**Sewage, Domestic (Domestic Wastes)** - Liquid wastes from the non-commercial preparation, cooking, and handling of food, liquid wastes containing human excrement and similar matter from the sanitary conveniences in dwellings, commercial buildings, industrial buildings, and institutions, or liquid wastes from clothes washing and/or floor/wall washing. Therefore, domestic sewage includes both black water and grey water. (See Sewage, Sanitary.)

**Sewage, Normal** - Sewage, industrial wastes, or other wastes, which show, by analysis, the following characteristics:

- B.O.D. (Five Day) - 2090 lbs. per million gallons (250 milligrams per liter), or less.
- Suspended Solids - 2500 lbs. per million gallons (300 milligrams per liter), or less.
- Phosphorus - 125 lbs. per million gallons (15 milligrams per liter), or less
- Ammonia - 250 lbs. per million gallons (30 milligrams per liter), or less.

- Total Kjeldahl Nitrogen - 417 lbs. per million (50 milligrams per liter), or less.
- Chlorine Demand - 209 lbs. per million gallons (25 milligrams per liter), or less.
- Chemical Oxygen Demand - 2920 lbs. per million gallons (350 milligrams per liter), or less.
- Oil and Grease - 830 lbs. per million gallons (100 milligrams per liter), or less

In spite of satisfying one or more of these characteristics, if the sewage also contains substances of concern, it may not be considered normal sewage.

**Sewage, Sanitary** - Liquid wastes from the sanitary conveniences of dwellings (including apartment houses and hotels), office buildings, factories, or institutions, which is free from storm water, surface water, industrial, and other wastes. (See Domestic Wastes.)

**Sewage Treatment Plant (Water Pollution Control Plant)** - see POTW Treatment Plant.

**Sewage, Unusual Strength or Character** - Sewage which has concentrations greater than those of Normal Sewage and /or which contains Substances of Concern.

**Sewer** - A pipe or conduit for carrying or transporting sewage.

**Sewer, Combined** - A sewer designed to receive and transport both surface runoff and sewage.

**Sewer, Public** - A sewer in which all abutting property owners have equal rights, and the use of which is controlled by the City of Port Jervis.

**Sewer, Sanitary** - A sewer which carries sewage, and to which storm, surface, and groundwaters are not intentionally admitted.

**Sewer, Storm (Storm Drain)** - A sewer which carries storm and surface waters and drainage, but excludes sewage and industrial wastewaters, other than cooling waters and other unpolluted waters.

**Sewerage System**- All facilities for collecting, regulating, pumping, and transporting wastewater to and away from the POTW Treatment Plant.

**Sewerage Surcharge** - The demand payment for the use of a public sewer and/or sewage treatment plant for the handling of any sewage, industrial wastes, or other wastes accepted for admission thereto in which the characteristics thereof exceed the maximum values of such characteristics in normal sewage. (See Volume Charge.)

**Significant Industrial User** - see User, Significant Industrial.

**Significant Non-Compliance (SNC)** - A User is in significant non-compliance if its violation(s) meet(s) one or more of the following criteria:

- Chronic violations of wastewater discharge limits, defined here as those, in sixty-six (66) percent or more of all of the measurements taken during a six-month period, which exceed (by any magnitude) the daily maximum limit or average limit for the same pollutant parameter;
- Technical Review Criteria (TRC) violations, defined here as those, in which thirty-three (33) percent or more of all of the measurements for each pollutant parameter taken during a six-month period, which equal or exceed the product of the daily maximum limits multiplied by the applicable TRC (TRC = 1.4 for BOD, TSS, fats, oil and grease; TRC = 1.2 for all other pollutants);
  - Any other violation of a pretreatment effluent limit (daily maximum or long-term average) that the Director determines has caused, alone or in combination with other discharges, interference or pass through (including endangering the health of POTW personnel or the general public);
  - Any discharge of a pollutant that has caused imminent endangerment to human health, welfare or to the environment or has resulted in the Director's exercise of its emergency authority under Article 11 of this Law;
  - Failure to meet, within 90 days after the schedule date, a compliance schedule milestone contained in a local control mechanism or enforcement order for starting construction, completing construction, or attaining final compliance;
  - Failure to provide, within 30 days after the due date, required reports such as baseline monitoring reports, 90-day compliance reports, periodic self-monitoring reports, and reports on compliance with compliance schedules;
  - Failure to report accurately any non-compliance;
  - Any other violation that the Director determines will adversely affect the implementation or operation of the local pretreatment program.

**Slug** - A substantial deviation from normal rates of discharge or constituent concentration (see normal sewage) sufficient to cause interference. In any event, a discharge which, in concentration of any constituent or in quantity of flow, that exceeds, for any period of duration longer than fifteen (15) minutes, more than five (5) times the average twenty-four (24) hour concentration or flow during normal user operations, shall constitute a slug.

**Standard Industrial Classification (SIC)** - A classification pursuant to the Standard Industrial Classification Manual issued by the Executive Office of

the President, Office of Management and Budget, 1972, and subsequent revisions.

**Standard Methods** - Procedures contained in the latest edition of "Standard Methods for the Examination of Water and Wastewater", published by the American Public Health Association, procedures established by the Administrator, pursuant to Section 304 (G) of the Act and contained in 40 CFR, Part 136, and amendments thereto. (If 40 CFR, Part 136 does not include a sampling or analytical technique for the pollutant in question, then procedures set forth in EPA publication, "Sampling and Analysis Procedures for Screening of Industrial Effluents for Priority Pollutants", April 1977, and amendments thereto, shall be used.), any other procedure approved by the Administrator, or any other procedure approved by the Director, whichever is the most conservative.

**State** - State of New York.

**State's Waters** - See Waters of the State.

**Storm Water** - Any flow occurring during or following any form of natural precipitation; also the flow resulting therefrom.

**Substances of Concern** - Those compounds which the New York State Department of Environmental Conservation has determined may be harmful to humans or the environment.

**Sump Pump** - A mechanism used for removing water from a sump or wet well.

**Suspended Solids** - The result obtained, using an approved laboratory procedure, to determine the dry weight of solids, in a sample, that either float on the surface of, or are in suspension, or are settleable, and can be removed from the sample by filtration, expressed in milligrams per liter.

**Total Kjeldahl Nitrogen (TKN)** - The result obtained, using an approved laboratory procedure, to determine the quantity of ammonia in a sample and released during the acid digestion of organic nitrogen compounds, expressed as milligrams of nitrogen per liter.

**Total Phosphorus** - The result obtained, using an approved laboratory procedure, to determine the total quantity of orthophosphate, in a sample of wastewater, following the hydrolysis of phosphorus compounds, expressed as milligrams of phosphorus per liter of sample.

**Toxic Substances** - Any substance, whether gaseous, liquid, or solid, that when discharged to a public sewer in sufficient quantities may be hazardous to POTW operation and maintenance personnel, tend to interfere with any

biological sewage treatment process, or to constitute a hazard to recreation in the receiving waters, due to the effluent from a sewage treatment plant or overflow point. Any pollutant or combination of pollutants listed as toxic in regulations promulgated by the EPA under provisions of CWA 307 (A), or other Acts.

**User** - Any person who contributes, causes, or permits the contribution of wastewater into the POTW.

**User Charge** – See Volume Charge.

**User, Existing** - A discharger to the POTW who is discharging on or before the effective date of this Law.

**User, Industrial** - A discharger to the POTW who discharges non-domestic wastewaters.

**User, New** - A discharger to the POTW who initiates discharge after the effective date of this Law.

**User, Significant Industrial (SIU)** - An industrial user of the City Of Port Jervis POTW who is:

- Subject to National Categorical Pretreatment Standards promulgated by the EPA,
- Having substantial impact, either singly or in combination with other industries, on the operation of the treatment works,
- Using, on an annual basis, more than 10,000 lbs or 1,000 gallons of raw material containing priority pollutants and/or substances of concern and discharging a measurable quantity of these pollutants to the sewer system,
- Discharging more than five percent (5%) of the flow or load of conventional pollutants received by the POTW treatment plant.

\*Note: A user discharging a measurable quantity of a pollutant may be classified as non-significant if, at the influent to the POTW treatment plant, the pollutant is not detectable.

**Volume Charge (User Charge)** – The demand sewer use charge which is based, in part or wholly, on the volume of normal sewage discharged into the POTW (there may be surcharges, as provided for in Article 12). The volume charge shall be based on a specific cost per 100 cubic feet or per 1,000 gallons. The specific charge set by resolution of the City of Port Jervis Common Council pursuant to Section 280 – 10 of the City Code. The moneys so obtained shall be used for current operation and maintenance, for retirement of bonded indebtedness, and for funding of capital projects, of the POTW Collection System (POTWCS). The basis of volume charge calculations shall be made available to the public, on demand, as provided in Article 13.

The volume charge shall be recalculated annually, as well as the surcharge rates.

**Wastewater** - The liquid and water-carried industrial or domestic wastewaters from dwellings, commercial establishments, industrial facilities, and institutions, together with any groundwater, surface water, and storm water that may be present, whether treated or untreated, which is contributed into or permitted to enter the POTW.

**Wastewater Discharge Permit** - A permit as set forth in Article 10 of this Law.

**Wastewater, Unusual Strength or Character** - see Sewage, Unusual Strength or Character.

**Waters of the State (State's Waters)** - All streams, lakes, ponds, marshes, water courses, waterways, wells, springs, reservoirs, aquifers, irrigation systems, drainage systems, and all other bodies or accumulations of water, surface or underground, natural or artificial, public or private, which are contained within, flow through, or border upon the State or any portion thereof.

## **Section 202 - Abbreviations**

The following abbreviations shall have the designated meanings:

ANSI - American National Standards Institute  
ASTM - American Society for Testing and Materials  
AWWA - American Water Works Association  
BOD - Biochemical Oxygen Demand  
CFR - Code of Federal Regulations  
CPLR - Code of Public Law and Rules  
COD - Chemical Oxygen Demand

DEP or NYCDEP – New York City Department of Environmental Protection  
DPW – City of Port Jervis Department of Public Works

EPA - Environmental Protection Agency  
L - Liter  
Mg - Milligram  
Mg/l - Milligrams per liter  
NCPI - National Clay Pipe Institute  
NPDES - National Pollutant Discharge Elimination System  
NYSDEC - New York State Department of Environmental Conservation  
NYSDOH - New York State Department of Health  
NYSDOT - New York State Department of Transportation  
P - Total Phosphorus

PSI - Pounds per Square Inch  
POTW - Publicly Owned Treatment Works

POTWCS – Publicly Owned Treatment Works Collection System  
PPM - Parts per Million, weight basis  
SIC - Standard Industrial Classification  
SPDES - State Pollutant Discharge Elimination System  
SWDA - Solid Waste Disposal Act, 42 U.S.C. 690 L, et seq.  
U.S.C. - United State Code of Laws  
USEPA - United State Environmental Protection Agency  
TSS - Total Suspended Solids

**Section 203 - Undefined Terms** Terms not defined in this article, or terms found to be ambiguous or improperly defined in this article, shall be defined by the Act, or Regulations, pursuant thereto.

### **Article 3**

#### **Use of Public Sewers Required**

Section 301 - Waste Disposal Unlawful  
Section 302 - Connecting Private Sewage System to Storm Sewer Unlawful  
Section 303 - Discharge of Sewage into Well Prohibited  
Section 304 - Wastewater Discharge Unlawful  
Section 305 - Building Permit Allowed Only When Approved Wastewater Disposal Available  
Section 306 - Private Wastewater Disposal Unlawful  
Section 307 - Connection to Public Sewer Required  
Section 308 - Limitation on Use of Public Sewers  
Section 309 – Reserved  
Section 310 - Moratorium  
Section 311 - Basis of Sewer Use Requirement  
Section 312 – Exceptions to Connection to Public Sewer

**Section 301 - Waste Disposal Unlawful** It shall be unlawful for any person to place, deposit, or permit to be deposited, in any unsanitary manner, on public or private property, within the City of Port Jervis or in any area under the jurisdiction of the said municipality, any human or animal excrement, garbage, or objectionable waste. Also, no person shall discharge domestic sewage onto the surface of the ground or discharge it in a way that permits it to come to the surface of the ground.

#### **Section 302 - Connecting Private Sewage System to Storm Sewer Unlawful**

No person shall connect a private sewage system so that sewage flows into a storm sewer or into a drain intended exclusively for storm water.

#### **Section 303 - Discharge of Sewage into Well Prohibited**

No person shall discharge sewage into a well.

**Section 304 - Wastewater Discharge Unlawful** It shall be unlawful to discharge to any natural outlet, within the City of Port Jervis, or in any area under the jurisdiction of the said municipality, any wastewater or other polluted waters, except where suitable treatment has been provided in accordance with subsequent provisions of this Law.

**Section 305 - Building Permit Allowed Only When Approved Wastewater Disposal Available** No property owner, builder, or developer shall be issued a building permit for a new dwelling or structure requiring sanitary facilities unless a suitable and approved method of wastewater disposal, conforming to this Law, is available. Except as provided in Sections 312 and Section 401, all housing construction or building development which takes place after this Law is enacted shall provide for an approved system of sanitary sewers.

**Section 306 - Private Wastewater Disposal Unlawful** Except as hereinafter provided in Section 312 and in Article 4, it shall be unlawful to construct or maintain any privy, privy vault, cesspool, septic tank, or other facility intended or used for disposal of wastewater.

**Section 307 - Connection to Public Sewer Required** The owner(s) of all houses, buildings, or properties used for human occupancy, employment, recreation, or other purposes, situated within the City of Port Jervis, and abutting on any street, alley, or right-of-way in which there is now located or may, in the future, be located a public sewer, is hereby required, at the owner's expense to install suitable sanitary facilities therein, and to connect such facilities directly with the proper public sewer, in accordance with the provisions of this law, within ninety (90) days after official notice to do so, provided that said public sewer is within one hundred (100) feet (30.5 meters) of the property line.

**Section 308 - Limitation on Use of Public Sewers** The use of the City of Port Jervis public sewers shall be strictly limited and restricted, except as provided in Section 307, to receive and accept the discharge of sewage and other wastes, including industrial wastes generated on or discharged from real property within the bounds of the Service Area of the POTW.

**Section 309 - Reserved**

**Section 310 – Moratorium** Upon the recommendation of the Director, who determines that:

- one or more segments of the POTW is exceeding its hydraulic capacity at any time
- any specific purpose of this Law is being violated



The City Of Port Jervis Common Council shall have the authority to limit or deny new connections to the POTW until the conditions leading to the moratorium have been corrected. Such correction may be by:

- construction of new facilities
- enlarging existing facilities
- correction of inflow and infiltration
- cleaning and repairing of existing facilities

The DEP may recommend to the Director that he study the need for a moratorium and that he make a recommendation to the Common Council.

**Section 311 - Basis of Sewer Use Requirement** All requirements, directives, and orders calling for mandatory use of the sewers, within the Service Area of the POTW, for the proper discharge of sewage and other wastes, including industrial wastes, shall be established and given by the City of Port Jervis Common Council, NYSDEC, USEPA, and/or by the Director and/or other such State or Federal agencies, which have enforcement powers.

**Section 312 - Exceptions to Connection to Public Sewer** Under certain circumstances, an exception to Section 307 may be permitted for construction and maintenance of certain private septic systems, privy vaults, septic tanks, cesspools or other types of wastewater disposal systems or facilities, which are of a design which has been approved by the Director and the City Planning Board and which meet the standards and requirements of the Building and Sanitary Codes of the City of Port Jervis, as well as the requirements for an exception to connection to the public sewer under this Law. This Section 312 provision may apply in those circumstances when the public sewer system is not within 100 feet (30.5 meters) of the property line or in other special circumstances when hookup to the public sewer system may not be feasible but construction of another type of wastewater system will meet the City's Building and Sanitary Codes.

## **Article 4**

### **Private Wastewater Disposal**

Section 401 - Public Sewer Unavailable - Private Wastewater Disposal Required

Section 402 - Connection of Two Buildings to the Same Septic Tank Prohibited

Section 403 - Construction Permit Application

Section 404 - Construction Permit

Section 405 - Preventing Nuisances - Rehabilitation Required

Section 406 - Sanitary Operation Required

Section 407 - Septage Removal

Section 408 - Direct Connection to New Public Sewers Required  
Section 409 - Additional Requirements

**Section 401 - Public Sewer Unavailable - Private Wastewater Disposal Required** Where a public sewer is not available, under the provisions of Section 304, the building lateral shall be connected to a private wastewater disposal system complying with the provisions of the Rules and Regulations of the NYSDOH, to be enforced by the Director, and/or the Orange County Health Department.

**Section 402 - Connection of Two Buildings to the Same Septic Tank Prohibited** No two separate permanent buildings, where the intended use for either is for a distinct and separate business or a dwelling place for a private family or families, shall be connected to the same individual septic tank and tile absorption field.

**Section 403 - Construction Permit Application** A completed application form, in compliance with the requirements of the City's Building Code, the City's Sewers and Sewage Disposal Code and this Sewer Use Law, as well as the appropriate application fees and escrow deposits (if any) shall be submitted to the City Clerk-Treasurer, 20 Hammond Street. At a minimum, to meet the requirements of this Law, the application shall contain the results of percolation tests, computations, and a plot plan, including the design and cross-section of the wastewater disposal system, in relation to lot lines, adjacent and on-site well or water supply, and buildings. Any fee, established by Article 12, shall accompany the application. The wastewater disposal system shall be designed by a professional engineer, and shall be in accordance with the NYSDOH - "Standards for Waste Treatment Works", or NYSDEC "Standards for Commercial and Institutional Facilities", as appropriate.

**Section 404 - Construction Permit** A written construction permit shall be obtained from the Director before construction commencement. The Director and Building Official, or his designated representative, shall be permitted to inspect the construction work at any stage, without prior notice.

**Section 405 - Preventing Nuisances - Rehabilitation Required** When the liquid or liquid-borne effluent from a private wastewater disposal system enters any watercourse, ditch, storm sewer, or water supply system, located in the City of Port Jervis, in such a manner, volume, and concentration so as to create a hazardous, offensive, or objectionable condition, in the opinion of the Director, the Orange County Health Department, or the NYSDOH, the owner of the premises upon which such wastewater disposal system is located, upon receiving written notice from the Director, to do so, shall, within ninety (90) days, after receipt of such notice, repair, rebuild, or relocate such wastewater disposal system for the purpose of eliminating such hazardous, offensive, or objectionable conditions. The repair, rebuilding, or relocation of the system shall be accomplished in accordance with the rules

and regulations of the NYSDOH and the Orange County Health Department, at the owner's expense.

**Section 406 - Sanitary Operation Required** The owner shall operate and maintain the private wastewater disposal system in a satisfactory manner at all times, at the owner's expense.

**Section 407 - Septage Removal** Where a private wastewater disposal system utilizes a cesspool or a septic tank, septage shall be removed from the cesspool or septic tank, by a licensed hauler of trucked and hauled wastes, at three year intervals or more frequently.

**Section 408 - Direct Connection to New Public Sewers Required** At such time that a public sewer becomes available to a property, a direct connection shall be made to the public sewer, in compliance with this Law, and any cesspool, septic tank, and similar wastewater disposal facilities shall be cleaned of septage, by a licensed septage hauler, and finally either filled with clean sand, bank-run gravel, or dirt, or removed and properly disposed. When the connection is made to the public sewer, the connection to the private wastewater disposal facility shall be broken and both ends of the break shall be plugged, as appropriate. If at any time, in the opinion of the Director, and upon the Director's notice to the owner(s), that a private septic tank, cesspool or other alternative waste disposal system has failed and when the public sewer line is within one hundred (100) feet (30.5 meters) of the property so affected, the owner(s) of said property shall be required to connect to the public sewer system in compliance with Section 307.

**Section 409 - Additional Requirements** No statement in this Article shall be construed to prevent, or interfere with, any additional requirements that may be deemed necessary by the Director to protect public health and public welfare.

## **Article 5**

### **New Sewers or Sewer Extensions**

Section 501 - Proper Design

Section 502A - New Sewers Subject to Approval, Fees, Inspection, Testing, and Reporting

Section 502B - Plans, Specification, and Pipe Test Results Required

Section 503A - Gravity Sewer Pipe

Section 503B - Safety and Load Factors

Section 503C - Sewer Pipe Installation

Section 503D - Cleanout Installation

Section 504 - Manholes and Manhole Installation

Section 505A - Low Pressure Air Testing

Section 505B - Test Section

Section 505C - Pipe Lamping

Section 505D - Deflection Testing

Section 505E – Vacuum Testing  
Section 506A - Force Mains  
Section 506B - Force Main Testing  
Section 507 - Final Acceptance and Warranty/Surety  
Section 508 - Liability Insurance Coverage During Construction Period

**Section 501 - Proper Design** New sanitary sewers and all extensions to sanitary sewers owned and operated by the City of Port Jervis shall be designed by a professional licensed to practice sewer design in the State in accordance with the Recommended Standards for Sewage Works, as adopted by the Great Lakes - Upper Mississippi River Board of State Sanitary Engineers ("Ten State Standards"), and in strict conformance with all requirements of the NYSDEC, and the current New York State Building Code. Plans and specifications shall be submitted to, and written approval shall be obtained from the Director, the Orange County Health Department, and the NYSDEC, before initiating any construction. The design shall anticipate and allow for flows from all possible future extensions or developments within the immediate drainage area

If, however, there is inadequate capacity in any sewer that would convey the wastewater, the application shall be denied. Sewer line and current use shall be defined as the present use and the unutilized use which has been committed, by resolution, to other users by the City of Port Jervis Common Council.

**Section 502 A - New Sewers Subject to Approval, Fees, Inspection, Testing, and Reporting** When a property owner, builder, or developer proposes to construct sanitary sewers or extensions to sanitary sewers in an area proposed for subdivision, the plans, specifications, and method of installation shall be subject to the approval of the Director, and the Orange County Health Department, in accordance with Section 501. Said property owner, builder, or developer shall pay for the entire installation, including a proportionate share of the intercepting or trunk sewers, and all other City of Port Jervis expenses incidental thereto. The owner, builder or developer shall prepare an Engineering Study as prepared by a New York State Licensed Engineer delineating that downstream facilities are adequate for the increased tributary flows. Each street lateral shall be installed and inspected pursuant to Article 6. The applicant shall pay the inspection fees prior to initiating construction. Design and installation of sewers shall be as specified in Section 503, and in conformance with Paragraphs 3 through 6 of ASTM Specification C-12. The installation of the sewer shall be subject to periodic inspection by the Director, without prior notice at the expense of the property owner. The Director shall determine whether the work is proceeding in accordance with the approved plans and specifications, and whether the completed work will conform to the approved plans and specifications. The sewer, as constructed, between the house connection and cleanout must pass the lower pressure air test required in Section 505, before any building lateral is connected thereto. Sections that cannot be tested must be visually

observed by the Director. The Director shall be notified 30 days in advance of the start of any construction actions so that such inspection frequencies and procedures as may be necessary or required, may be established. No new sanitary sewers will be accepted by the City of Port Jervis Common Council until such construction inspections have been made so as to assure the City of Port Jervis Common Council of compliance with this Law and any amendments or additions thereto. The Director has the authority to require such excavation as necessary to inspect any installed facilities if the facilities were covered or otherwise backfilled before they were inspected so as to permit inspection of the construction. The Director shall report all findings of inspections and tests to the City of Port Jervis Common Council.

**Section 502 B - Plans, Specification, and Pipe Test Results Required**

Plans, specifications, and methods of installation shall conform to the requirements of this Article. Components and materials of wastewater facilities not covered in this Law, such as pumping stations, lift stations, or force mains shall be designed in accordance with Section 501, and shall be clearly shown and detailed on the plans and specifications submitted for approval. Force main details are covered in Section 506. When requested, the applicant shall submit, to the Director and to the County Health Department, all design calculations and other pertinent data to supplement review of the plans and specifications. Results of manufacturer's tests on each lot of pipe delivered to the job site shall also be furnished, upon request.

**Section 503 A - Gravity Sewer Pipe** Sewer pipe material shall be:

- Cast Iron Pipe - Extra Heavy
  - Pipe, fittings, and specials shall conform to the requirements of ASTM Specification A-74 or ANSI A-21.11.
  - Gaskets shall conform to ASTM Specification C-564.
- Polyvinyl Chloride (PVC) Pipe – SDR 35
  - Pipe shall be made from Class 12454-B materials or better in accordance with ANSI/ASTM Specification D-1784.
  - Pipe and accessories shall conform to the requirements of the following, with a minimum pipe stiffness of 46.
  - PSI at a maximum deflection of five percent (5%).
  - ANSI/ASTM D 3034 (4" - 15")
  - ASTM F 679 Type I (18" - 27")

- Ductile Iron Pipe
  - Pipe, fittings, and specials shall be manufactured in accordance with ASTM Specification A-746.
  - Pipe shall have a minimum thickness of Class 51.
  - Fittings shall conform to ANSI Specification A-21.11 and have a minimum pressure class rating of 150 PSI.
  - All pipe and fittings shall be cement mortar lined in accordance with ANSI Specification A-21.4 at twice the specified thickness, and have an internal and external bituminous seal coating.
  - Closure pieces shall be jointed by means of a mechanical coupling of the cast sleeve type.
  
- Other pipe materials
  - Other pipe materials require prior written approval of the Director before being installed.
    - The minimum internal pipe diameter shall be eight (8) inches for gravity sewers and three (3) inches for low pressure sewers.
    - Joints for the selected pipe shall be designed and manufactured such that "O" ring gaskets of the "snap-on" type are used.
    - Gaskets shall be continuous, solid, natural or synthetic rubber, and shall provide a positive compression seal in the assembled joint, such that the requirements of Section 505 are met.
    - Joint preparation and assembly shall be in accordance with the manufacturer's recommendations.
    - Wye branch fittings or saddle connections, as approved by the Director, shall be installed, for connection of street laterals, in accordance with Section 606.

### **Section 503 B - Safety and Load Factors**

Selection of pipe class shall be predicated on the following criteria:

Safety factor - 1.5

Load factor - 1.7

Weight of soil - 120 lbs/cu. ft.

Wheel loading - 16,000 lbs.

Utilizing the foregoing information, design shall be made as outlined in Chapter IX of the Water Pollution Control Federation Manual of Practice No. 9, latest edition, "Design and Construction of Sanitary and Storm Sewers", and the pipe shall have sufficient structural strength to support all loads to be placed on the pipe, with a safety factor as specified above.

PVC pipe shall not be encased in concrete due to their different coefficients of linear thermal expansion.

## **Section 503 C - Sewer Pipe Installation**

(1) Local utilities shall be contacted to verify construction plans and to make arrangements to disconnect all utility services, where required to undertake the construction work. The utility services shall later be reconnected. The work shall be scheduled so that there is minimum inconvenience to local residents. Residents shall be provided 48 hours notice regarding disconnection of utilities.

(2) The construction right-of-way shall be cleared only to the extent needed for construction. Clearing consists of removal of trees which interfere with construction, removal of underbrush, logs, and stumps, and other organic matter, removal of refuse, garbage, and trash, removal of ice and snow, and removal of telephone and power poles, and posts. Any tree that will not hinder construction shall not be removed, and shall be protected from damage by any construction equipment. Debris shall not be burned, but hauled for disposal in an approved manner.

(3) The public shall be protected from personal and property damage as a result of the construction work.

(4) Traffic shall be maintained at all times in accordance with applicable highway permits. Where no highway permits are required, at least 1/2 of a street shall be kept open for traffic flow.

(5) Erosion control shall be performed throughout the project to minimize the erosion of soils onto lands or into waters adjacent to or affected by the work. Erosion control can be effected by limiting the amount of clearing and grubbing prior to trenching, proper scheduling of the pipe installation work, minimizing time of open trench, prompt grading and seeding, and filtration of drainage.

(6) The trench shall be excavated only wide enough for proper installation of the sewer pipe, manhole, and appurtenances. Allowances may be made for sheeting, de-watering, and other similar actions to complete the work. Roads, sidewalks, and curbs shall be cut, by sawing or by other methods as approved by the Director, before trench excavation is initiated.

(7) Under ordinary conditions, excavation shall be by open cut from the ground surface. However, tunneling or boring under structures other than buildings may be permitted. Such structures include crosswalks, curbs, gutters, pavements, trees, driveways, and railroad tracks.

(8) Open trenches shall be protected at all times of the day with barricades, as required.

(9) Trenches shall not be open for more than 30 feet in advance of pipe installation nor left unfilled for more than 30 feet in the rear of the installed

pipe, when the work is in progress, without permission of the Director. When work is not in progress, including over night, weekends, and holidays, the trench shall be backfilled to ground surface.

(10) The trench shall be excavated approximately six (6) inches deeper than the final pipe grade. When unsuitable soils are encountered, these shall be excavated to a maximum depth of 2-1/2 feet below the final pipe invert grade and replaced with select materials.

(11) Ledge rock, boulders, and large stones shall be removed from the trench sides and bottom. The trench shall be over-excavated at least 12 inches for five (5) feet, at the transition from rock bottom to earth bottom, centered on the transition.

(12) Maintenance of grade, elevation, and alignment shall be done by some suitable method or combination of methods.

(13) No structure shall be undercut unless specifically approved by the Director.

(14) Proper devices shall be provided, and maintained operational at all times, to remove all water from the trench. At no time shall the sewer line be used for removal of water from the trench.

(15) To protect workers and to prevent caving, shoring and sheeting shall be used, as needed. Caving shall not be used to backfill the trench. Sheeting shall not be removed but cut off no lower than one foot above the pipe crown and no higher than one foot below final grade, and left in the trench, during backfill operations.

(16) The pipe barrel shall be supported, along its entire length, on a minimum of six (6) inches of crusher run, max. 1/2 inch stone free of organic material. This foundation shall be firmly tamped in the excavation.

(17) Bell holes shall be hand excavated, as appropriate.

(18) Pipe shall be laid from low elevation to high elevation. The pipe bell shall be up-gradient; the pipe spigot shall be down-gradient.

(19) Joint preparation and assembly shall be in accordance with the manufacturer's written instructions.

(20) The grade and alignment shall be checked and made correct. The pipe shall be in straight alignment. Any negotiation of curves shall be at manholes.



(21) When a smaller sewer joins a larger one the invert of the larger sewer shall be lowered sufficiently to maintain the same hydraulic gradient. An approximate method which may be used for securing this result is to place the 0.8 depth of both sewers at the same elevation.

(22) Crushed stone shall be placed over the laid pipe to a depth of at least six (6) inches. The embedment of thermoplastic pipe shall be in accordance with ASTM D2321 using class 1A or 1B backfill materials. Care shall be exercised so that stone is packed under the pipe haunches. Care shall be exercised so that the pipe is not moved during placement of the crushed stone.

(23) The migration of fines from surrounding backfill or native soils shall be restricted by gradation of embedment materials or by use of suitable filter fabric.

(24) The remaining portion of the trench above the pipe embedment shall be backfilled in 12 inch lifts which shall be firmly compacted. Compaction near/under roadways, driveways, sidewalks, and other structures shall be with NYSDOT Type IV subbase and to 95 % of the maximum moisture-density relationship, as determined by ASTM Specification D 698, Method D. Ice, snow, or frozen material shall not be used for backfill.

### **Section 503 D - Cleanout Installation**

(1) Cleanouts for low pressure sewers shall be placed at intervals of approximately 400 to 500 feet, at major changes of direction, where one collection main joins another main and at the upstream end of each main branch.

(2) The design of the cleanouts shall be as approved by the Director.

### **Section 504 - Manholes and Manhole Installation**

(1) Design of all manholes shall be submitted to the Director and shall receive approval prior to placement.

(2) Manholes shall be placed where there is a change in slope or alignment, and at intervals not exceeding 400 linear feet except as authorized by the Director.

(3) Manhole bases shall be constructed or placed on a minimum of six (6) inches of crushed stone max. 1/2 inch stone free of organic materials.

(4) Manhole bases shall be constructed of 4,000 psi (28 day) concrete 8 inches thick, or shall be precast bases properly bedded in the excavation.

Field constructed bases shall be monolithic, properly reinforced, and extend at least 6 inches beyond the outside walls of lower manhole sections. Precast manhole bases shall extend at least 6 inches beyond the outside walls of lower manhole sections. Manholes shall be installed level.

(5) Manholes shall be constructed using precast minimum 4 foot diameter concrete manhole barrel sections, and an eccentric top section, conforming to ASTM Specification C-478, with the following exceptions on wall thickness:

<b>Manhole Diameter (Feet)</b>	<b>Wall Thickness (Inches)</b>
4	5
5	6
6	7
6 ½	7 1/2
7	8
8	9

All sections shall be cast solid, without lifting holes.

Flat top slabs shall be a minimum of 8 inches thick and shall be capable of supporting a H-20 loading.

(6) All joints between sections shall be sealed with an "O" ring rubber gasket, meeting the same specifications as pipe joint gaskets, or butyl joint sealant completely filling the joint.

(7) All joints shall be sealed against infiltration. All metal parts shall be thickly coated with bitumastic or elastomeric compound to prevent corrosion.

(8) No steps or ladder rungs shall be installed inside or outside manhole walls at any time.

(9) No holes shall be cut into the manhole sections closer than 6 inches from joint surfaces.

(10) Manholes that extend above grade shall not have an eccentric top section. The top plate shall be large enough to accommodate the cover lifting device and the cover.

(11) The elevation of the top section shall be such that the cover frame top elevation is 0.5 foot above the 100-year flood elevation (in a field), 0.5 foot above a lawn elevation, or at finished road or sidewalk grade.

(12) When located in a traveled area (road or sidewalk), the manhole frame and cover shall be heavy duty cast iron. When located in a lawn or in a field, the manhole frame and cover may be light duty cast iron. The cover shall be 24 inches, minimum, in diameter. The mating surfaces shall be machined, and painted with tar pitch varnish. The cover shall not rock in the frame. Infiltration between the cover and frame shall be prevented by proper design and painting. Covers shall have "Sanitary Sewer" cast into them. Covers shall have lifting holes suitable for any lifting/jacking device. The lifting holes shall be designed so that infiltration is prevented.

(13) A drop of at least 0.1 foot shall be provided between incoming and outgoing sewers on all junction manholes and on manholes with bends greater than 45 degrees.

(14) Inverts and shelves/benches shall be placed after testing the manholes and sewers.

(15) Benches shall be level and slope to the flow channel at about 1 inch per foot.

(16) The minimum depth of the flow channel shall be the nominal diameter of the smaller pipe. The channel shall have a steel trowel finish. The flow channel shall have a smooth curvature from inlet to outlet.

(17) Manhole frames, installed at grade, shall be set in a full bed of mortar with no less than two nor more than four courses of brick underneath to allow for later elevation adjustment. In lieu of brick, grade rings may be used for elevation adjustment. Grade rings shall not exceed 6 inches in depth. The total number of grade rings shall not exceed 12 inches in height, however, in no event shall more than 3 grade rings be used.

(18) Manholes which extend above grade, shall have the frames cast into the manhole top plate. The top plate shall be securely anchored to the manhole barrel, by a minimum of six 1/2 inch corrosion resistant anchor bolts, to prevent overturning when the cover is removed. The anchor bolts shall be electrically isolated from the manhole frame and cover.

(19) Internal drop pipes and fittings shall be PVC plastic sewer pipe in compliance with ASTM D2241. Corrosion resistant anchors shall be used to attach the drop pipe to the inside surface of the manhole barrel. Internal drops shall not be permitted in manholes less than 5' in diameter.

(20) Outside drop manholes may be permitted with approval from the Director.

(21) Where a new connection must be installed, it shall be machine rotary cored and shall not be hammered, chiseled or made by linear cutting or impact tools.

(22) All connections shall be by Elastomeric Boot, specifically designed and supplied for such connections.

### **Section 505 A - Low Pressure Air Testing**

Low pressure air tests shall conform to ASTM Specification F1417-11a (Standard Practice for Installation Acceptance of Plastic Non-Pressure Sewer Lines Using Low-Pressure Air) or latest revision. All sections to be tested shall be cleaned and flushed, and shall have been backfilled, prior to testing. Air shall be added until the internal pressure of the test section is raised to approximately 4.0 PSIG. The air pressure test shall be based on the time, measured in seconds, for the air pressure to drop from 3.5 PSIG to 2.5 PSIG.

Acceptance is based on limits tabulated in the "Specification Time Required for a 1.0 PSIG Pressure Drop" in the Uni-Bell PVC Pipe Association "Recommended Practice For Low-Pressure Air Testing of Installed Sewer Pipe".

Before pressure is applied to the line all connections shall be firmly plugged. Before the test period starts, the air shall be given sufficient time to cool to ambient temperature in the test section.

If the test section is below groundwater, the test pressure shall be increased by an amount sufficient to compensate for groundwater hydrostatic pressure, however, the test pressure shall not exceed 9 PSI, or a lower pressure as required by the Director.

The pressure test gauge shall have been recently calibrated, and a copy of the calibration results shall be made available to the Director prior to testing.

### **Section 505 B - Test Section**

The test section shall be from manhole structure to manhole structure. All connections and service laterals to be plugged and braced adequately to withstand the test pressure before starting the test.

### **Section 505 C - Pipe Lamping**

When approved by the Director, pipe lamping may be substituted for deflection testing as provided in Section 505D. Prior to testing, the section shall be lamped. Any length of pipe out of straight alignment shall be realigned.

### **Section 505 D - Deflection Testing**

Also prior to testing, all plastic pipe, in the test section, shall be tested for deflection. Deflection testing shall involve the pulling of a rigid ball or

mandrel, whose diameter is 95 percent of the pipe inside diameter, through the pipe. Any length of pipe with a deflection greater than 5 percent shall be replaced. The test section shall be flushed just prior to deflection testing. The test shall not be performed with a mechanical pulling device.

**Section 505 E - Vacuum Testing**

Vacuum testing shall be employed for testing of all manholes and shall conform to ASTM C1244-11 (Standard Test Method for Concrete Sewer Manholes by the Negative Air Pressure (Vacuum) Test Prior to Backfill) or latest revision. All manholes to be tested shall be cleaned and flushed, and shall have been backfilled, prior to testing. The vacuum test shall be based on the time, measured in seconds, for the vacuum to decrease from 10 inches of mercury to 9 inches of mercury for manholes.

Acceptance of manholes is based on the following:

Manhole Depth	Manhole Diameter	Time to Drop 1 inch Hg (10"to9")
10 ft or less	4 ft	120 seconds
10 ft to 15 ft	4 ft	150 seconds
15 ft to 25 ft	4 ft	180 seconds

For 5 ft diameter manholes, add 30 seconds to the times above.

For 6 ft diameter manholes, add 60 seconds to the times above.

See Tables in ASTM C1244-11 for additional diameters, depths and test times.

Manholes shall be tested from castings.

If the test on the manhole fails (the time is less than that tabulated above), necessary repairs shall be made and the vacuum test repeated, until the manhole passes the test.

The vacuum test gauge shall have been recently calibrated, and a copy of the calibration results shall be made available to the Director prior to testing.

**Section 506A - Force Mains**

Force mains serving sewage lifting devices, such as grinder pumps and pump stations, shall be designed in accordance with Section 501. Additional design requirements are:

(1) Force main pipe material shall be:

(a) Ductile Iron Pipe

Pipe shall conform to ANSI A21.51 and ASTM 746-03. The minimum wall thickness shall be Class 52 (ANSI A21.50). The pipe shall be clearly marked with either "D" or "DUCTILE". Fittings shall conform to ANSI A21.10.

Pipe and fittings shall be furnished with push-on joints conforming to ANSI A21.11.

Pipe and fittings shall be cement mortar lined and have an internal and external bituminous seal coating.

(b) Polyvinyl Chloride (PVC) Plastic Pipe

Pipe shall conform to ASTM D2241. Materials used in the manufacture of PVC pipe shall meet ASTM C1784. The minimum wall thickness shall be SDR-21. Fittings shall conform to ASTM D2241. Joints and gaskets shall conform to ASTM D2241, D1869, and F477.

(c) Other pipe materials

Other pipe materials require prior written approval of the Director before being installed.

(2) Trenching, bedding, and backfilling shall be in accordance with Section 503 C.

(3) Joint preparation and assembly shall be in accordance with the manufacturer's written instructions.

(4) Anchorages, concrete blocking, and/or mechanical restraint shall be provided when there is a change of direction of 7-1/2 degrees or greater. All restrains shall be as designed by a Professional Engineer registered in New York State.

(5) Drain valves shall be placed at low points.

(6) Automatic air relief valves shall be placed at high points.

(7) Air relief and drain valves shall be suitably protected from freezing.

(8) When the daily average design detention time, in the force main, exceeds 20 minutes, the manhole and sewer line receiving the force main discharge or the sewage shall be treated so that corrosion of the manhole and the

exiting line are prevented. The corrosion is caused by sulfuric acid biochemically produced from hydrogen sulfide anaerobically produced in the force main.

(9) The force main shall terminate, in the receiving manhole, at a PVC plastic sewer pipe "T". The vertical arms of the "T" shall be twice the diameter of the force main. The upper arm shall be at least 4 feet long; the lower arm shall terminate in a PVC plastic sewer pipe 90 degree elbow in a flow channel directed to the manhole exit pipe. The "T" and its arms shall be securely fastened to the inside surface of the manhole wall using corrosion resistant anchors.

### **Section 506B - Force Main Testing**

All force mains shall be subjected to hydrostatic pressure of 150 percent of the normal operating pressure. The duration of the test, at pressure, shall be at least 2 hours. Before conducting the test, the pipe shall be filled with water and all air shall be expelled. During the test, water shall be added, as needed, to maintain the test pressure. The amount of water added shall be recorded so as to calculate leakage. Leakage shall not exceed 25 gallons per day per mile per inch nominal pipe diameter. During the test, the owner and the Director shall walk the route of the force main and examine the exposed pipe and the ground covering any backfilled pipe to discover leaks. Leakage in excess of that specified above shall be corrected with new material at the owner's expense and the test repeated. Any observed leaks shall be repaired at the owner's expense. Each test section length shall be as approved by the Director, but in no event longer than one thousand (1,000) feet.

### **Section 507 - Final Acceptance and Warranty/Surety**

All sanitary sewers and extensions to sanitary sewers constructed at the applicant's expense, after final approval and acceptance by the Director, and concurrence by the City of Port Jervis Common Council, shall become the property of the City of Port Jervis, and shall thereafter be operated and maintained by the City of Port Jervis. No sanitary sewer shall be accepted by the City of Port Jervis, until four (4) copies of as-built drawings have been so filed with the Director and the Director has approved the submitted drawings. Said sewers, after their acceptance by the City of Port Jervis, shall be guaranteed against defects in materials or workmanship for one (1) year, by the applicant. The guarantee shall be in such form and contain such provision as deemed necessary by the City of Port Jervis Common Council, secured by a surety bond or such other security as the City of Port Jervis Common Council may approve.

### **Section 508 - Liability Insurance Coverage During Construction Period**

(1) All contractors engaged in connecting house laterals with sanitary sewers, who perform any work within the Right of Way of any highway, shall file a financial security in a form acceptable to the Director in the amount of the improvements to be constructed with the City of Port Jervis Clerk to indemnify the City of Port Jervis against loss, cost, damage or expense sustained or recovered on account of any negligence, omission or act of the applicant for such a permit, or any of his, or their agents arising or resulting directly or indirectly by reason of such permit or consent, or of any act, construction or excavation done, made or permitted under authority of such permit or consent. All financial security shall contain a clause that permits given by the City of Port Jervis Common Council may be revoked at any time for just cause.

2) Before commencing work, the above contractor shall file insurance certificates with the City of Port Jervis Clerk for the following:

(a) Workman's Compensation and Employer's Liability Insurance as required by the laws of the State covering the contractor;

(b) Personal Injury Liability having limits of not less than \$500,000 each occurrence and \$500,000 aggregate (completed operations/products, personal injury);

(c) Property Damage Liability having limits of not less than \$500,000 for all damages arising during the life of the contract; and shall include, but not be limited to, the following designated hazards:

- i - Premises and Operations;
- ii - Independent Contractors;
- iii - Completed operations and products;
- iv - Property Damage; and
- v - Explosions, collapse and underground;

(d) Comprehensive automobile liability (including non-owned and hired automobiles) having limits of not less than:

- i - Bodily injury - each person, \$300,000  
- each occurrence, \$500,000
- ii - Property damage - each occurrence, \$500,000

(e) Business Excess Liability Insurance in the amount of \$2,000,000.

(f) All insurance policies must provide for five (5) business days notice to the City of Port Jervis before cancellation and must cover all liabilities of the City of Port Jervis and be in a form approved by the City of Port Jervis Common Council and be in a satisfactory form approved by the Council.



(g) The minimum insurance limits shall be established and amended by resolution of the City of Port Jervis Common Council.

(3) Where it is necessary to enter upon or excavate any highway or cut any pavement, sidewalk or curbing, permission must be obtained from the Director of Public Works if a City of Port Jervis street is involved, from the County Department of Public Works if a County Highway is involved, and/or the New York State Department of Transportation if a State Highway is involved.

(4) The minimum insurance limits stated above shall be as established by the City of Port Jervis Common Council and shall be subject to periodic review and adjustment, as appropriate, by resolution of the City of Port Jervis Common Council.

## **Article 6**

### **Building Laterals, Street Laterals Connections, and Fees**

Section 601A - Permit Required for Sewer Connections

Section 601B - Inflow/Infiltration Prohibited

Section 602 - Sewer Lateral Permits

Section 603A - New Building Laterals

Section 603B - Laterals Serving Several Buildings

Section 603C - Laterals Serving Complexes

Section 603D - Dry Sewers

Section 604 - Using Existing Building Laterals

Section 605 - Lateral Pipe Materials

Section 606A - Street Lateral to Public Sewer Connection

Section 606B - Future Connection Locations; As-Built Drawings

Section 606C - Special Manhole Requirements

Section 607 - Laterals At and Near Buildings

Section 608 - Sewage Lifting

Section 609 - Lateral Pipe Installation

Section 610A - Watertight Joints

Section 610B - Cast Iron Push Joints

Section 610C - PVC Push Joints

Section 611A - Building Lateral/Street Lateral Connection

Section 611B - Cleanout Repair/Replacement

Section 611C - Street Lateral Replacement; Ownership

Section 612 - Testing

Section 613A - Connection Inspection

Section 613B - Trench Inspections

Section 614 - Public Safety Provisions Required; Restoration of Disturbed Areas

Section 615 - Interior Clean-Out

Section 616 - Costs Borne by Owner

### **Section 601 A - Permit Required for Sewer Connections**

No unauthorized person shall uncover, make any connection with or opening into, use, alter, or disturb any public sewer or appurtenance thereof without first obtaining a written permit from the Director.

### **Section 601 B - Inflow/Infiltration Prohibited**

No person shall discharge or cause to be discharged any storm water, ground water, cooling water or unpolluted industrial waters to any sanitary sewer. Swimming pool drains shall not be connected to any sanitary sewer.

### **Section 602 - Sewer Lateral Permits**

There shall be two classes of sewer lateral permits:

- (1) For residential, commercial, and institutional service,
- (2) For service to establishments producing industrial wastes. In either case, a permit application shall be submitted to the Director. The permit application shall be supplemented by any plans, specifications, or other information considered pertinent, in the judgment of the Director. A fee, for residential, commercial, institutional and industrial users, as established by the City of Port Jervis Common Council, shall accompany the application.

Connections to existing manholes shall be made as directed by the Director.

### **Section 603 A - New Building Laterals**

A separate and independent building lateral shall be provided for every building requiring sanitary facilities.

New street laterals and/or building laterals shall not go under building basements. In like fashion, a building shall not be constructed over an existing lateral; the lateral shall be relocated after the Director has approved plans showing the relocation. If relocation is not physically possible then the lateral shall be:

- (1) exposed and totally encapsulated in not less than three inches of concrete, or
- (2) exposed and walled and the building rooms above positively ventilated outdoors.

All existing manholes in or under the basement shall be sealed air-tight in a manner acceptable to the Director. No new manholes shall be constructed on the portion of the lateral under the building.

### **Section 603 B -Laterals Serving Several Buildings**

When building laterals are to serve multiple dwelling structures, the building lateral shall be sized in accordance with the metered water use and with sound professional engineering judgment.

### **Section 603 C - Laterals Serving Complexes**

Where a lateral sewer is to serve a complex of industrial, commercial, institutional, or dwelling structures, special design of the building lateral system shall be required. Such lateral sewer shall be connected to the public sewer through a manhole. The Director shall determine if and where this connection to the public sewer is required. If required, a new manhole shall be installed in the public sewer pursuant to Sections 504 and 1007 and the lateral connection made and tested as directed by the Director. Plans and specifications shall be prepared and submitted for approval pursuant to this Law.

### **Section 603 D - Dry Sewers**

Dry Sewers shall be designed and installed in accordance with this Law.

### **Section 604 - Using Existing Building Laterals**

Existing building laterals may be used in connection with new buildings only when they are found, on examination by the Director, to meet all requirements of this local Law.

### **Section 605 - Lateral Pipe Materials**

Building and street lateral pipe materials shall be one of the following:

1) Tar-coated, service grade, cast iron soil pipe conforming to ASTM Specification A-74, "Cast Iron Pipe and Fittings". All dimensions, weight and markings of the pipe shall conform to the requirements of ANSI, Designation A112.5.1, except spigot ends shall be "plain end", if gasket joints are used.

(2) Polyvinyl chloride (PVC) pipe and fittings conforming to ASTM Specification D-3034-73, "SDR-35 Polyvinyl Chloride (PVC) Sewer Pipe and Fittings". All pipe shall be suitable for gravity sewer service. Provisions shall be made for contraction and expansion at each joint with a rubber ring. The bell shall consist of an integral wall section stiffened with two PVC retainer rings that securely lock the solid cross-section ring into position. Minimum

"Pipe Stiffness" (F/Y) at five percent (5%) deflection shall be 46 PSI when tested in accordance with ASTM Specification D-2412.

Any part of the building or street lateral that is located within five (5) feet of a water main or water service shall be constructed of cast iron soil pipe. Cast iron soil pipe may be required by the Director where the building or street lateral is likely to be damaged by tree roots. If installed on fill or unstable ground, the building or street lateral shall be of cast iron soil pipe, although other pipe material may be permitted if such pipe is uniformly supported on a poured concrete cradle approved by the Director. The distance between consecutive joints, as measured along the centerline of the installed pipe, shall not be less than ten (10) feet, except under abnormal circumstances, in which case this dimension may be diminished, if approved by the Director. The size and slope of building and street laterals shall be subject to approval by the Director, but in no event shall the internal pipe diameter be less than 4 inches, nor shall the pipe slope be less than 1/4 inch per foot.

### **Section 606 A - Street Lateral to Public Sewer Connection**

At the point of connection of a street lateral to a main sewer, a standard wye fitting and sufficient one-eighth (45 degree) bend fittings shall be used. The wye fittings shall be installed so that flow in the "arm" shall transition smoothly into the flow in the public sewer. No lateral connection shall be made to the public sewer that permits the flow into the public sewer from the lateral to enter at right angles.

The inside diameter of the fittings shall be same diameter as the street lateral inside diameter.

### **Section 606 B - Future Connection Locations; As-Built Drawings**

The street lateral, including the wye and eighth bend fittings, shall be connected to the main sewer at the time of constructing the main sewer, for each proposed lot for either immediate or future development. Laterals installed for future development shall be fitted a standard plug approved for use by the Director. All sewer connections shall be via a properly installed saddle on the main sewer pipe. No portion of the lateral pipe shall protrude into the main sewer pipe. The location of all lateral connections shall be field marked with a sanitary wye and cleanout. The marker cleanout shall extend from the depth of the lateral to a minimum of two (2) feet above grade. The location of all lateral connections shall be indicated on a drawing with a minimum of three (3) tie lines indicated. Four (4) copies of this drawing, showing the as-built location of these connections, shall be furnished to the Director. A refundable deposit shall be placed with City of Port Jervis to assure receipt of these as-builts. The deposit shall be placed when application is made; the amount of the deposit shall be \$250 per sheet of plans showing locations of lateral connections. No sanitary sewer shall be accepted by City of Port Jervis until four (4) copies of this record drawing

have been so filed with the Director and the Director has approved the submitted drawings. Deposit fees may be revised from time to time by Resolution of the Port Jervis Common Council pursuant to City of Port Jervis Municipal Code Section 280 – 10.

### **Section 606 C - Special Manhole Requirements**

When any street lateral is to serve a school, hospital, or similar institution, or public housing, or is to serve a complex of industrial or commercial buildings, or which, in the opinion of the Director, will receive wastewater or industrial wastes of such volume or character that frequent maintenance of said building or street lateral is anticipated, then such street lateral shall be connected to the public sewer through a manhole. The Director shall determine if and where this type of connection to the public sewer is required. Connections to existing manholes shall be made as directed by the Director. If required, a new manhole shall be installed in the public sewer pursuant to Sections 504 and 1007, and the lateral connection made thereto as directed by the Director.

### **Section 607 - Laterals At and Near Buildings**

Building laterals laid parallel to a bearing wall shall not be installed closer than six (6) feet to such wall. The building lateral shall enter the basement through the basement wall no less than twelve (12) inches above the basement floor. In no event shall any building lateral be placed below the basement floor, except with the expressed written approval of the Director.

The building lateral shall be laid at uniform grade and in straight alignment. Changes in direction shall be made only with properly curved pipe and fittings. All changes in grade or alignment shall be made with a cleanout that extends to grade, terminating in a terminal box set in concrete. In building laterals, said cleanouts shall be provided such that the maximum distance between cleanouts is 50 feet unless the Director determines that a greater distance is necessary. The ends of all building or street laterals, which are not connected to the interior plumbing of the building, for any reason, shall be sealed against infiltration by a suitable stopper, plug, or by other approved means.

### **Section 608 - Sewage Lifting**

In all buildings in which any building drain is too low to permit gravity flow to the public sewer, wastewater carried by such drain shall be lifted by mechanical means and discharged to the building lateral, on approval of the Director.

### **Section 609 - Lateral Pipe Installation**

All excavations required for the installation of a building or street lateral shall be open trench work unless otherwise approved by the Director. Pipe laying and backfilling, regardless of pipe material used, shall be performed in general accordance with paragraphs 3 through 6 of ASTM Specification C-12, except that trench width, measured at the top of the installed pipe, shall not exceed the outside pipe diameter plus 14 inches and, except that no backfill shall be placed until the work has been inspected. The depth of cover over the pipe shall be sufficient to afford protection from frost, but not in any case shall such depth be less than four (4) feet. Where it is physically impossible to provide cover of four (4) feet, the depth may be reduced to a minimum of two (2) feet and the pipe shall be insulated, as approved by the Director.

### **Section 610 A - Watertight Joints**

All joints and connections shall be made watertight.

### **Section 610 B - Cast Iron Push Joints**

Pre-molded gaskets may be used for hub and plain end cast iron pipe joints and joints with fittings, if approved by the Director. The gasket shall be a neoprene compression-type unit which provides a positive seal in the assembled joint. The gasket shall be pre-molded, one-piece unit, designed for joining the cast iron hub and plain end soil pipe and fittings. The assembled joint shall be sealed by compression of the gasket between the exterior surface of the spigot and the interior surface of the hub. The joint shall be assembled following the manufacturer's recommendations using acceptable lubricant and special pipe-coupling tools designed for that purpose. The plain spigot end shall be forced into the hub end of the pipe for the full depth of the hub itself. Lubricant shall be a bland, flax-base, non-toxic material, and shall not chemically attack the gasket material.

### **Section 610 C - PVC Push Joints**

Joints for PVC sewer pipe shall follow the manufacturer's recommendations, using properly designed couplings and rubber gaskets pursuant to the published information relating thereto, and conforming to the applicable ASTM specification identified in Section 605.

### **Section 611 A - Building Lateral/Street Lateral Connection**

(1) The connection of the building lateral to an existing street lateral shall be made at the property line. Except as provided under Section 502, if a street lateral has not previously been provided, the street lateral will be constructed from the existing public sewer to the property line, by the DPW, unless otherwise directed by the Director, at the Owner's expense. The street lateral shall be installed with a properly sealed and covered clean-out to grade located at the property line. The clean-out shall terminate in a metal box imbedded in concrete.

(2) The cost of constructing the street lateral from the existing public sewer to the property line shall be at the property owner's expense; all subsequent costs and expense incidental to the installation and connection of the building lateral shall also be borne by the owner.

(3) The permit application shall require that the property owner shall indemnify the City of Port Jervis from any loss or damage that may directly or indirectly be occasioned by the installation of the building lateral.

(4) It shall be the responsibility of the property owner to maintain, repair, or replace the building/street lateral (from building to public sewer), as needed.

(5) The method of connection of the building lateral to the street lateral will be dependent upon the type of sewer pipe material, and, in all cases, shall be approved by the Director. After the installation of the street lateral has been approved by the Director, the building/street lateral shall remain the property of the building owner.

### **Section 611 B - Cleanout Repair/Replacement**

If, in the judgment of the Director, it is determined that a building lateral, without a property line clean-out, needs repair or replacement, the City of Port Jervis may install a clean-out at the property line, at the property owner's expense, such that the street lateral can be maintained independently of the building lateral.

### **Section 611 C - Street Lateral Replacement; Ownership**

Any existing street lateral which, upon examination by the Director, is determined to be in need of replacement shall be replaced with a new street lateral with a property line clean-out. The replacement street lateral shall be constructed by the DPW, unless otherwise directed by the Director. The cost of constructing the replacement street lateral and clean-out shall be at the property owner's expense. Once the replacement street lateral and clean-out have been constructed and approved by the Director, the new street lateral shall become the property of the property owner.

### **Section 612 – Testing**

The street lateral, building lateral, or the combined lateral shall be tested for infiltration/exfiltration by:

- (a) any full pipe method described in Section 505, or
- (b) by a suitable joint method, with the prior written approval of the Director.

### **Section 613 A - Connection Inspection**

In circumstances, as approved by the Director, when laterals are not installed by the DPW, the follow shall apply;

The applicant for the building lateral permit shall notify the Director when the building lateral is ready for inspection and connection is to be made to the street lateral. The connection shall be made under the supervision of the Director.

The applicant for the street lateral permit shall notify the Director when the street lateral is ready for inspection and connection is to be made to the main sewer. The connection shall be made under the supervision of the Director.

### **Section 613 B - Trench Inspections**

In circumstances, as approved by the Director, when laterals are not installed by the DPW, the follow shall apply;

When trenches are excavated for the laying of building lateral pipes or for the laying of street lateral pipes, such trenches shall be inspected by the Director, and or Building Official, as applicable. Before the trenches are backfilled, the person performing such work shall notify the Director and Building Official when the laying of the building lateral is completed, and no backfilling of trenches shall begin until approval is obtained from the Director or Building Official.

### **Section 614 - Public Safety Provisions Required; Restoration of Disturbed Areas**

All excavations for constructing building laterals shall be adequately protected with barricades and lights so as to protect the public from hazard. Streets, sidewalks, parkways, and other public property disturbed, in the course of the work, shall be restored in a manner satisfactory to the Director. When installation requires disturbance of paved public roads and shoulders, restoration shall involve backfilling to road grade. Shortly thereafter the City of Port Jervis Department of Public Works (DPW) shall complete road and shoulder restoration to the City of Port Jervis Standards. The cost for such final road and shoulder restoration by the DPW shall be included with the fees paid with the application for the permit required in Section 602.

### **Section 615 - Interior Clean-Out**

An interior clean-out fitting shall be provided for each building lateral at a readily accessible location, preferably just inside the basement wall. The fitting shall contain a 45-degree branch with removable plug or test tee, and so positioned that sewer cleaning equipment can be inserted therein to clean the building lateral.



The cleanout diameter shall be no less than the building lateral diameter.

### **Section 616 - Costs Borne by Owner**

All costs associated with the provisions of this Article shall be borne by the property owner unless specifically stated or agreed to be a cost borne by the City of Port Jervis. The permit application shall require that the property owner shall indemnify the City Of Port Jervis from any loss or damage that may be directly or indirectly occasioned by the installation of the building and street laterals, and connections and appurtenances. Insurance requirements and other forms of security to cover the work to be permitted may be revised from time to time by Resolution of the Port Jervis Common Council pursuant to City of Port Jervis Municipal Code Section 280 - 10.

## **Article 7**

### **Inflow**

Section 701 - New Inflow Sources Prohibited

Section 702 - Existing Inflow Sources Disconnected

Section 703 - Existing Inflow Sources Disconnected When Property Sold

Section 704 - No Re-connection of Inflow Source Allowed

Section 705 - Charges for Inflow

### **Section 701 - New Inflow Sources Prohibited**

No connections shall be made to a sanitary sewer which connections are intended to discharge inflow. Such prohibited connections include, but are not limited to, footing drains, roof leaders, roof drains, cellar drains, sump pumps, catch basins, uncontaminated cooling water discharges, or other sources of inflow.

### **Section 702 - Existing Inflow Sources Disconnected**

For properties where separate storm sewers are available within 100 feet of the property line or where, in the judgment of the Director, sufficient natural drainage is available, connections which contribute inflow to the sanitary sewers must be disconnected in a fashion approved by the Director, prior to the sale of the property.

### **Section 703 - Existing Inflow Sources Disconnected When Property Sold**

Upon notice from the Tax Assessor, the Building Official shall inspect any newly sold property for the purpose of determining if storm sewers or natural

drainage is available, and, if so, if all connections which contribute inflow have been disconnected.

#### **Section 704 - No Re-connection of Inflow Source Allowed**

It shall be a willful violation of this Law for any person to reconnect any inflow source that has been disconnected pursuant to this Article.

#### **Section 705 – Charges for Inflow**

The Superintendent may take whatever action is necessary to determine the amount of inflow from a property, including to require the installation of a control manhole. The property from which the inflow originated shall be billed for inflow according to Article 12, however the City of Port Jervis Council may approve the imposition of a surcharge at a rate not to exceed five (5) times that for normal sewage volume charge.

#### **Article 8 – RESERVED**

#### **Article 9 - Discharge Restrictions**

- Section 901 - Pretreatment Standards
- Section 902 - General Prohibitions
- Section 903 - Concentration Based Limitations
- Section 904 - Mass Discharge Based Limitations
- Section 905 - Modification of Limitations
- Section 906 - Access to User's Records
- Section 907 - Dilution
- Section 908 - Grease, Oil, and Sand Interceptors
- Section 909 - Solid Waste Grinders
- Section 910 - Rejection of Wastewater

#### **Section 901 - Pretreatment Standards**

All Users of the City of Port Jervis POTW will comply with all standards and requirements of the Act and standards and requirements promulgated pursuant to the Act, including but not limited to 40 CFR Parts 406 - 471.

#### **Section 902 - General Prohibitions**

No user shall contribute or cause to be contributed, in any manner or fashion, directly or indirectly, any pollutant or wastewater which will interfere with the operation or performance of the POTW. These general prohibitions apply to all such users of a POTW whether or not the user is subject to National Categorical Pretreatment Standards, or any other Federal, State, or Local Pretreatment Standards or Requirements.

Without limiting the generality of the foregoing, a User may not contribute the following substances to the POTW:

(1) Any solids, liquids, or gases which, by reason of their nature or quantity, are or may be sufficient, either alone or by interaction with other substances, to cause a fire or an explosion or be injurious, in any way, to the POTW, or to the operation of the POTW. At no time shall both of two successive readings on a flame type explosion hazard meter, at the point of discharge into the system (or at any other point in the system) be more than 25 % nor any single reading be more than 40 % of the lower explosive limit (LEL) of the meter. Unless explicitly allowable by a written permit, prohibited materials include, but are not limited to, gasoline, kerosene, naphtha, benzene, toluene, xylene, ethers, alcohols, carbides, hydrides, and sulfides, and any other substance which the City of New York, the City of Port Jervis, the State, or the EPA has determined to be a fire hazard, or hazard to the POTW.

2) Solid or viscous substances which may cause obstruction to the flow in a sewer or otherwise interfere with the operation of the wastewater treatment facilities. Unless explicitly allowable by a written permit, such substances include, but are not limited to, grease, garbage with particles greater than one-half (1/2) inch in any dimension, animal guts or tissues, paunch manure, bones, hair, hides or fleshings, entrails, whole blood, feathers, ashes, cinders, sand, spent lime, stone or marble dust, metal, glass, straw, shavings, grass clippings, rags, spent grains, spent hops, waste paper, wood, plastics, gas, tar asphalt residues, residues from refining or processing fuel or lubricating oil, mud, or glass or stone grinding or polishing wastes.

(3) Any wastewater having a pH less than 5.0 or greater than 10.0.

(4) Any wastewater containing toxic pollutants in sufficient quantity, either singly or by interaction with other pollutants (including heat), to injure or interfere with any wastewater treatment process, constitute a hazard to humans or animals, create a toxic effect in the receiving waters of the POTW, or to exceed the limitation set forth in a Categorical Pretreatment Standard.

A toxic pollutant shall include, but not be limited to, any pollutant identified pursuant to Section 307(A) of the Act.

(5) Any noxious or malodorous solids, liquids, or gases which either singly or by interaction with other wastes are sufficient to create a public nuisance or a hazard to life or are sufficient to prevent entry into the sewers for their maintenance or repair.

6) Oils and grease - Any commercial, institutional, or industrial wastes containing fats, waxes, grease, or oils which become visible solids when the wastes are cooled to ten (10) degrees centigrade (50 degrees fahrenheit); any petroleum oil, non-biodegradable cutting oil, or products of mineral oil

origin, in excess of 100 mg/l or in amounts that will cause interference or pass through.

7) Any wastewater that will cause interference or pass through.

(8) Any wastewater with objectionable color that is not removed in the treatment process, such as, but not limited to, dye wastes, and vegetable tanning solutions.

(9) Any solid, liquid, vapor, or gas having a temperature higher than 65 degrees C (150 degrees F); however, such materials shall not cause the POTW treatment plant influent temperature to be greater than 40 degrees C (104 degrees F). The Director reserves the right, in certain instances, to prohibit or limit the discharge of wastes whose maximum temperatures are lower than 65 degrees C.

(10) Unusual flow rate or concentration of wastes, constituting slugs, except by Industrial Wastewater Permit.

(11) Any wastewater containing any radioactive wastes except as approved by the Director, and in compliance with applicable State and Federal regulations.

(12) Any wastewater that causes a hazard to human life or that creates a public nuisance, either by itself or in combination, in any way, with other wastes.

(13) Any wastewater with a closed cup flashpoint of less than 140 degrees Fahrenheit or 60 degrees Centigrade using the test methods specified in 40 CFR Part 261.21.

(14) Any pollutants that result in the presence of toxic gases, vapors or fumes within the POTW in a quantity that may cause acute worker health and safety problems.

### **Section 903 - Concentration Based Limitations**

No User shall discharge, directly or indirectly, to the POTW, wastewater containing any of the following substances in concentrations exceeding those specified below, except by permit or as provided for in Section 904. Concentration limits are applicable to wastewater effluents at the point just prior to discharge into the sanitary sewer system ("end of pipe" concentrations).

### **EFFLUENT CONCENTRATION LIMITS**

<b>PARAMETER (1)</b>	<b>MAXIMUM CONCENTRATION (2) MG/L</b>
Acetone	20.7
Aluminum	1.7026
Ammonia	39
Arsenic	1.4930
Barium	0.2091
BOD(3)	500
Cadmium	0.0068
Chromium Hexavalent	0.1089
Chromium	0.0340
Copper	0.0610
Cyanide (Complex)	0.2990
Cyanide (Free)	0.0408
Ethyl Acetate	20.70
Iron	1.8283
Isopropyl Acetate	20.70
Lead	0.1160
Manganese	0.6853
Methyl Ethyl Ketone	60
Methylene Chloride	3.00
Molybdenum	12.05
n-amyl Acetate	20.70
Nickel	0.0878
Oil/Grease, Polar	100
Phenols (Total)	0.0176
Phenols (Chlorinated)	0.0141
Silver	0.2631
Sulfate	1,540
Toluene	100.00
Total Toxic Organics	2.13
UOD (3)	5,600
Xylene	0.0788
Zinc	0.1750

- (1) All concentrations listed for metallic substances shall be as "total metal", which shall be defined as the value measured in a sample acidified to a pH value of 2 or less, without prior filtration.
- (2) As determined on a composite sample taken from the User's daily discharge over a typical operational and/or production day, except for cyanide, total phenols, pH, oil and grease which shall be determined using grab samples.
- (3) As determined by an average of composite samples within a one month period.

The limits for pollutants other than those listed in this section and higher than the minimum detection limits as established by 40 CFR Part 136 and/or the current edition of Standard Methods shall be set on a case-by-case basis.

4) Other substances which may be limited are:

alkanes, alkenes and alkynes

aliphatic and aromatic alcohols and acids

aliphatic and aromatic aldehydes and ketones

aliphatic and aromatic esters

aliphatic and aromatic halogenated compounds

aliphatic and aromatic nitro, cyano and amino compounds

antibiotics

benzene derivatives

chemical compounds which, upon acidification, alkalization, oxidation or reduction, in the discharge or after admixture with wastewater and its components in the POTW, produce toxic, flammable, or explosive compounds

pesticides, including algicides, fungicides, herbicides, insecticides,

rodenticides

phthalates

polyaromatic and polynuclear hydrocarbons

total toxic organics, TTO, as defined in 40 CFR 433.11

toxic organic compounds regulated by Federal Pretreatment Standards

unsaturated aliphatics, including those with an aldehyde, ketone or nitrile functional group

viable pathogenic organisms from industrial processes or hospital procedures

#### **Section 904 - Mass Discharge-Based Limitations**

The Director, in consultation with DEP, may impose mass discharge-based limits on individual Users for specific pollutants. Mass discharge-based limits may be imposed for pollutants that may have negative impact on the employees, the POTW or the receiving water. The Director shall issue permits to Significant Industrial Users and may issue permits to other Industrial Commercial Users limiting the discharge of these substances. Each permit shall restrict the discharge from each Significant Industrial User to a portion of the total allowable influent loading.

Permits issued in accordance with this section may allow for discharges in excess of concentration limitations set forth in this Sewer Use Law, if the concentrations and mass discharges do not interfere with the operation and performance of the POTW as recommended by the DEP and determined by the Director.

### **Section 905 - Modification of Limitations**

Limitations on wastewater strength or mass discharge contained in this Law may be supplemented with more stringent limitations when, in the opinion of the Director and upon recommendation from DEP:

- (1) The limitations in this Law are not sufficient to protect the POTW,
- (2) The limitations in this Law are not sufficient to enable the POTW treatment plant to comply with applicable water quality standards or the effluent limitations specified in the POTW's SPDES permit,
- (3) The POTW sludge will be rendered unacceptable for disposal or reuse as the DEP or the City of Port Jervis desires, as a result of discharge of wastewaters at the above prescribed concentration limitations,
- (4) Municipal employees or the public will be endangered, or
- (5) Air pollution and/or groundwater pollution will be caused.

The limitations on wastewater strength or mass discharge shall be recalculated by the Director not less frequently than once every five (5) years. The Director shall solicit the recommendations of the DEP in making these recalculations. The results of these calculations shall be reported to the City of Port Jervis Common Council and to DEP for review and recommendations. The Director shall make a calculation for submission to the Common Council. This Law shall then be amended appropriately by the Common Council. Any issued industrial wastewater discharge permits which have limitations based directly on any limitations that were changed shall be revised and amended, as appropriate.

### **Section 906 - Access to User's Records**

The Director and DEP shall have the authority to copy any record related to wastewater discharges to the POTW.

### **Section 907 - Dilution**

Except where expressly authorized to do so by an applicable Pretreatment Standard, no User shall ever increase the use of process water or, in any

other way, attempt to dilute a discharge as a partial or complete substitute for adequate treatment to achieve compliance with a Pretreatment Standard.

Dilution flow shall be considered to be Inflow.

### **Section 908 - Grease, Oil, and Sand Interceptors**

Grease, oil, and sand interceptors shall be provided when, in the opinion of the Director and at the recommendation of DEP, they are necessary for the proper handling of wastewater containing excessive amounts of grease, flammable substances, sand, or other harmful substances; except that such interceptors shall not be required for private living quarters or living units. All interceptors shall be of type and capacity approved by the Director and shall be so located to be easily accessible for cleaning and inspection. Such interceptors shall be inspected, cleaned, and repaired regularly, as needed, by the owner, at his expense.

### **Section 909 - Solid Waste Grinders**

Solid waste grinders at or serving commercial establishments, institutions or industries shall not discharge into the POTW if there is a combined sewer overflow (CSO) on the sewer lines conveying the wastes to the POTW treatment plant.

### **Section 910 - Rejection of Wastewater**

The City of Port Jervis Common Council shall reject a User's wastewater, on recommendation of the Director or the DEP, and when it is has been determined by the Common Council that the wastewater contains substances or possesses characteristics that have a deleterious effect on the POTW and its processes or on the receiving water, or which constitute a public nuisance or hazard. See Section 1016.

## **Article 10**

### **Discharge Permits And Pretreatment Requirements**

Section 1001 - Wastewater Discharge Reports

Section 1002 - Notification to Industrial Users

Section 1003 A - Wastewater Discharges

Section 1003 B - Wastewater Discharge Permits Required For Significant Industrial Users

Section 1003 C - Other Industrial Users

Section 1003 D - Discharge Permits to Storm Sewers Not Authorized

Section 1004 A - Application for Wastewater Discharge Permits

Section 1004 B - Permit Modifications



Section 1004 C - Permit Conditions  
Section 1004 D - Permit Duration  
Section 1004 E - Permit Reissuance  
Section 1004 F - Permit Transfer  
Section 1004 G - Permit Revocation  
Section 1004 H - Reserved  
Section 1005 - Reporting Requirements for Permittee  
Section 1006 - Flow Equalization  
Section 1007 - Monitoring Stations (Control Manholes)  
Section 1008 - Proper Design and Maintenance of Facilities and Monitoring Stations  
Section 1009 - Vandalism, Tampering with Measuring Devices  
Section 1010 - Sampling and Analysis  
Section 1011 - Accidental Discharges; SPCC Plan  
Section 1012 - Posting Notices  
Section 1013 - Sample Splitting  
Section 1014 - Public Access to Information Maintained by the Director  
Section 1015 A - Access to Property and Records  
Section 1015 B - Access to Easements  
Section 1015 C - Liability of Property Owner  
Section 1016 - Special Agreements

### **Section 1001 – Wastewater Discharge Reports**

As a means of determining compliance with this Law, with applicable SPDES permit conditions, and with applicable State and Federal law, each industrial user shall be required to notify the Director and DEP of any new or existing discharges to the POTW by submitting a completed Industrial Chemical Survey (ICS) form and a completed Industrial Wastewater Survey (IWS) form to the Director and to DEP. The Director and/or DEP may require any User discharging wastewater into the POTW to file wastewater discharge reports and to supplement such reports as the Director and/or DEP deems necessary. All information shall be furnished by the user to the Director and the DEP.

### **Section 1002 - Notification to Industrial Users**

The Director shall, from time to time, notify each Industrial User of applicable Pretreatment Standards, and of other applicable requirements under Section 204(B) and Section 405 of the Clean Water Act, and Subtitles C and D of RCRA.

### **Section 1003 A - Wastewater Discharges**

No Significant Industrial User shall discharge wastewater to the POTW without having a valid Wastewater Discharge Permit, issued by the Director. Significant Industrial Users shall comply fully with the terms and conditions of their permits in addition to the provisions of this Law. Violation of a permit term or condition is deemed a violation of this Law.

### **Section 1003 B - Wastewater Discharge Permits Required For Significant Industrial Users**

All Significant Industrial Users proposing to connect to or to discharge to the POTW shall obtain a Wastewater Discharge Permit before connecting to or discharging to the POTW. Existing significant industrial users shall make application for a Wastewater Discharge Permit within 30 days after the effective date of this Law, and shall obtain such a permit within 90 days after making application.

### **Section 1003 C - Other Industrial Users**

The Director may issue, in consultation with DEP, Wastewater Discharge Permits to other industrial users of the POTW.

### **Section 1003 D - Discharge Permits to Storm Sewers Not Authorized**

The City of Port Jervis does not have the authority to issue permits for the discharge of any wastewater to a storm sewer. This authority rests with the NYSDEC.

### **Section 1004 A - Application for Wastewater Discharge Permits**

All Industrial Users required to obtain a Wastewater Discharge Permit shall complete and file with the Director an application in the form prescribed by the City of Port Jervis, the application shall be accompanied by a fee, as set forth in Section 1203. In support of any application, the Industrial User shall submit, in units and terms appropriate for evaluation, the following information:

- (1) Name, address, and location (if different from the address).
- (2) SIC code of both the industry and any categorical processes.
- (3) Wastewater constituents and characteristics including but not limited to those mentioned in Article 10 of this Law and which are limited in the appropriate Categorical Standard, as determined by a reliable analytical laboratory approved by the NYSDOH. Sampling and analysis shall be performed in accordance with Standard Methods.
- (4) Time and duration of the discharge.
- (5) Average daily peak wastewater flow rates, including daily, monthly, and seasonal variations, if any.
- (6) Site plans, floor plans, mechanical and plumbing plans, and details to show all sewers, sewer connections, and appurtenances.

- (7) Description of activities, facilities, and plant processes on the premises, including all materials which are or could be discharged to the POTW.
- (8) Each product produced by type, amount, process or processes, and rate of production.
- (9) Type and amount of raw materials processed (average and maximum per day).
- (10) Number and type of employees, and hours of operation, and proposed or actual hours of operation of the pretreatment system.
- (11) The nature and concentration of any pollutants in the discharge which are limited by any County, State, or Federal Standards, and a statement whether or not the standards are being met on a consistent basis and if not whether additional Operation and Maintenance (O&M) and/or additional pretreatment is required for the user to meet all applicable Standards.
- (12) If additional pretreatment and/or O&M will be required to meet the Standards, then the industrial user shall provide the shortest schedule to accomplish such additional treatment and/or O&M. The completion date in this schedule shall not be longer than the compliance date established for the applicable Pretreatment Standard. The following conditions shall apply to this schedule:
  - (a) The schedule shall contain progress increments in the form of dates for the commencement and completion of major events leading to the construction and operation of additional pretreatment required for the user to meet the applicable Pretreatment Standards (such events include hiring an engineer, completing preliminary plans, completing final plans, executing contracts for major components, commencing construction, completing construction, beginning operation, and beginning routine operation).
  - (b) No increment referred to in (a) above shall exceed 9 months, nor shall the total compliance period exceed 18 months.
  - (c) No later than 14 calendar days following each date in the schedule and the final date for compliance, the user shall submit a progress report to the Director including, as a minimum, whether or not it complied with the increment of progress to be met on such date and, if not, the date on which it expects to comply with this increment of progress, the reason for delay, and the steps being taken by the user to return to the established schedule. In no event shall more than 9 months elapse between such progress reports to the Director.
- (13) Any other information as the Director or DEP may deem necessary to evaluate the permit application.

The Director shall provide a copy of the complete application as well as any supplemental information to DEP for review. Both DEP and the Director will evaluate the data furnished by the Industrial User and may require additional information. DEP shall forward comments and recommendations, and when appropriate, may submit a draft Wastewater Discharge Permit to the Director within thirty (30) days of receipt of the full application. After evaluation and acceptance of the data furnished, the City of Port Jervis may issue a Wastewater Discharge Permit to the Industrial User, subject to terms and conditions provided herein.

Under circumstances where the Director refers the application for Engineering Review, all costs associated with the review shall be borne by the permittee by establishment of an escrow account.

### **Section 1004 B - Permit Modifications**

Wastewater Discharge Permits may be modified by the Director, upon 30 days notice to the permittee, for just cause. Just cause shall include, but not be limited to:

- (1) Promulgation of an applicable National Categorical Pretreatment Standard,
- (2) Revision of or a grant of a variance from such categorical standards pursuant to 40 CFR 403.13,
- (3) Changes in general discharge prohibitions and local limits as per Section 903 of this law,
- (4) Changes in processes used by the permittee, or changes in discharge volume or character,
- (5) Changes in design or capability of any part of the POTW,
- (6) Discovery that the permitted discharge causes or contributes to pass through or interference, and
- (7) Changes in the nature and character of the sewage in the POTW as a result of other permitted discharges.

(8) Upon notification from DEP that any of the above have occurred.

Any changes or new conditions in the permit shall include a reasonable time schedule for compliance as set forth in Section 1004 A (12)(a).

The Director and DEP will evaluate the data furnished by the Industrial User and may require additional information. The Director shall provide a copy of the complete data and application to DEP for review. DEP shall forward comments and recommendations to the Director within thirty (30) days of receipt of the data and application. After evaluation and acceptance of the data furnished, the City of Port Jervis may issue a modified Wastewater Discharge Permit to the Industrial Users, subject to terms and conditions provided herein.

Under circumstances where the Director refers the application for Engineering Review, all costs associated with the review shall be borne by the permittee by establishment of an escrow account.

### **Section 1004 C - Permit Conditions**

Wastewater Discharge Permits shall be expressly subject to all the provisions of this Law, and all other applicable regulations, user charges and fees established by the City of Port Jervis. Permits may contain the following:

- (1) Limits on the average and maximum rate and time of discharge, or requirements for flow regulation and equalization.
- (2) Limits on the average and maximum wastewater constituents and characteristics, including concentration or mass discharge limits.
- (3) The unit charge or schedule of user charges and fees for the management of the wastewater discharged to the POTW.
- (4) Requirements for installation and maintenance (in safe condition) of inspection and sampling facilities.
- (5) Specifications for monitoring programs which may include sampling locations, frequency of sampling, number, types, and standards for tests, and reporting schedules.
- (6) Compliance schedules
- (7) Requirements for submission of technical reports or discharge reports.
- (8) Requirements for maintaining and retaining plant records relating to wastewater discharge, as specified by the City of Port Jervis, and affording the Director and DEP access thereto.
- (9) Requirements for notification of the City of Port Jervis Director and DEP of any new introduction of wastewater constituents or of any substantial change in the volume or character of the wastewater constituents being introduced into the POTW.
- (10) Requirements for the notification of the Director and DEP of any change in the manufacturing and/or pretreatment process used by the permittee.
- (11) Requirements for timely notification of excessive, accidental, or slug discharges.
- (12) Other conditions as deemed appropriate by the City of Port Jervis to ensure compliance with this Law, and State and Federal laws, rules, and regulations.

#### **Section 1004 D - Permit Duration**

Permits shall be issued for a specified time period, not to exceed five (5) years. A permit may be issued for a period less than five (5) years.

#### **Section 1004 E - Permit Reissuance**

The User shall apply for permit reissuance a minimum of 180 days prior to the expiration of the User's existing permit. The terms and conditions of the permit may be subject to modification by the Director, in consultation with DEP, during the term of the permit, as limitations or requirements, as identified in Section 1004 B, or other just cause exists. The User shall be informed of any proposed changes in its permit at least 30 days prior to the effective date of the change. Any changes or new conditions in the reissued permit shall include a reasonable time schedule for compliance as established in Section 1004 A (12)(a).

#### **Section 1004 F - Permit Transfer**

Wastewater Discharge Permits are issued to a specific User for a specific operation or discharge at a specific location. A Wastewater Discharge Permit shall not be reassigned, transferred, or sold to a new owner, new User, different premises, or a new or changed operation.

### **Section 1004 G - Permit Revocation**

Wastewater Discharge Permits may be revoked by the Director for the following reasons: falsifying self-monitoring reports, tampering with monitoring equipment, refusing to allow the Director or DEP timely access to the industrial premises, upon recommendation by DEP, failure to meet effluent limitations, failure to pay fines, failure to pay user charges, and failure to meet compliance schedules.

### **Section 1004 H – Reserved**

### **Section 1005 - Reporting Requirements for Permittee**

The reports or documents that are required to be submitted or maintained under this section shall be subject to:

- (a) The provisions of 18 USC Section 1001 relating to fraud and false statements;
- (b) The provisions of Sections 309(c)(4) of the Act, as amended, governing false statements, representation or certification; and
- (c) The provisions of Section (c)(6) of the Act, as amended, regarding corporate officers.

#### **1) Baseline Monitoring Report**

All permittees shall submit all reports required by this Section to the Director and to the DEP.

Within 180 days after promulgation of an applicable Federal Categorical Pretreatment Standard, a User subject to that standard shall submit, to the Director, the information required by paragraphs (8) and (9) of Section 1004 A.

#### **(2) 90-Day Compliance Report**

Within 90 days following the date for final compliance with applicable Pretreatment Standards, or, in the case of a New Source, following commencement of the introduction of wastewater into the POTW, any User subject to Pretreatment Standards and Requirements shall submit, to the Director and the DEP, a report indicating the nature and concentration of all pollutants in the discharge, from the regulated process, which are limited by Pretreatment Standards and Requirements, and the average and maximum

daily flow for these process units in the User's facility which are limited by such Pretreatment Standards and Requirements. The report shall state whether the applicable Pretreatment Standards and Requirements are being met on a consistent basis, and, if not, what additional O&M and/or pretreatment is necessary to bring the User into compliance with the applicable Pretreatment Standards or Requirements. This statement shall be signed by an authorized representative of the Industrial User, and certified to by a qualified professional.

### (3) Periodic Compliance Reports

a) Any User subject to a Pretreatment Standard, after the compliance date of such Pretreatment Standard, or, in the case of a New Source, after commencement of the discharge into the POTW, shall submit to the Director and DEP, during the months of June and December, unless required more frequently in the Pretreatment Standard or by the Director and DEP, a report indicating the nature and concentration of pollutants in the effluent which are limited by such Pretreatment Standards. In addition, this report shall include a record of all daily flows which, during the reporting period, exceeded the average daily flow reported in Section 1004 A. At the discretion of the Director and concurrence of DEP, and in consideration of such factors as local high or low flow rates, holidays, budget cycles, etc., the Director may agree to alter the months during which the above reports are to be submitted, however, no fewer than two reports shall be submitted per year.

(b) The Director with the concurrence of DEP may impose mass limitations on Users, which are using dilution to meet applicable Pretreatment Standards or Requirements, or, in other cases where the imposition of mass limitations are appropriate. In such cases, the report required by Section 1005 (3) (a) shall indicate the mass of pollutants regulated by Pretreatment Standards in the effluent of the User. These reports shall contain the results of discharge sampling and analysis, including the flow, and the nature and concentration, or production and mass, where requested by the Director and DEP, of pollutants contained therein, which are limited by the applicable Pretreatment Standard. All analyses shall be performed in accordance with Standard Methods, by a laboratory certified by NYSDOH to perform the analyses.

### (4) Violation Report

If sampling performed by the User indicates a violation of this Law and/or the User's discharge permit, the User shall notify the Director and DEP within 24 hours of becoming aware of the violation. The User shall also repeat the sampling and analysis and submit the results of the repeat analysis to the Director and DEP within 30 days after becoming aware of the violation. The User is not required to re-sample if the POTW performs monitoring of the User's discharge at least once a month for the parameter that was violated,

or if the POTW performs sampling, for the parameter which was violated, between the User's initial sampling and when the User receives the results of this sampling.

(5) Other reports

The Director may impose reporting requirements equivalent to the requirements imposed by Section 1005(3) for Users not subject to pretreatment standards.

**Section 1006 - Flow Equalization**

No person shall cause the discharge of slugs to the POTW. Each person discharging into the POTW greater than 100,000 gallons per day or greater than five percent (5%) of the average daily flow in the POTW, whichever is lesser, shall install and maintain, on his property and at his expense, a suitable storage and flow control facility to insure equalization of flow over a twenty-four (24) hour period. The storage and flow control facility shall have a capacity for at least fifty percent (50%) of the daily discharge volume and shall be equipped with alarms and a rate of discharge controller, the regulation of which shall be directed by the Director. A Wastewater Discharge Permit may be issued solely for flow equalization upon the same terms set forth elsewhere in this Law.

**Section 1007 - Monitoring Stations (Control Manholes)**

(a) All Significant Industrial Users, and other Industrial Users whose industrial waste discharge has caused or may cause Interference or Pass-Through shall install and maintain a suitable monitoring station, on their premises at their expense, to facilitate the observation, sampling, and measurement of their industrial wastewater discharge.

(b) If there is more than one street lateral serving an Industrial User, the Director may require the installation of a control manhole on each lateral.

(c) The Director may require that such monitoring station(s) include equipment for the continuous measurement and recording of wastewater flow rate and for the sampling of the wastewater. Such station(s) shall be accessibly and safely located, and the Industrial User shall allow immediate access, without prior notice, to the station by the Director and/or DEP, or either of their designated representatives.

**Section 1008 - Proper Design and Maintenance of Facilities and Monitoring Stations**

Preliminary treatment, and flow equalization facilities, or monitoring stations, if provided for any wastewater, shall be constructed and maintained



continuously clean, safe, and continuously operational by the owner at his expense. Where an Industrial User has such treatment, equalization, or monitoring facilities at the time this Law is enacted, the Director may approve or disapprove the adequacy of such facilities. Where the Director disapproves of such facilities and construction of new or upgraded facilities for treatment, equalization, or monitoring are required, plans and specifications for such facilities shall be prepared by a licensed professional engineer and submitted to the Director. Construction of new or upgraded facilities shall not commence until written approval of the Director has been obtained.

### **Section 1009 - Vandalism, Tampering with Measuring Devices**

No unauthorized person shall negligently break, damage, destroy, uncover, deface, tamper with, prevent access, or render inaccurate, or cause or permit the negligent breaking, damaging, destroying, uncovering, defacing, tampering with, preventing access, or rendering inaccurate to:

- i - any structure, appurtenance, or equipment which is a part of the City of Port Jervis POTW, or
- ii - any measuring, sampling, and/or testing device or mechanism installed pursuant to any requirement under this Law except as approved by the Director.

### **Section 1010 - Sampling and Analysis**

Sampling shall be performed so that a representative portion of the wastewater is obtained for analysis.

All measurements, tests, and analyses of the characteristics of waters and wastes required in any section of this Law shall be carried out in accordance with Standard Methods, by a laboratory certified by NYSDOH to perform the analyses. Such samples shall be taken at the approved monitoring stations described in Section 1007, if such a station exists. If an approved monitoring station is not required, then samples shall be taken from another location on the industrial sewer lateral before discharge to the public sewer. Unless specifically requested otherwise, or unless specifically not allowed in Federal regulation, samples shall be gathered as flow proportioned (where feasible) composite samples made up of individual samples taken not less than once per hour for the period of time equal to the duration of industrial wastewater discharge during daily operations (including any cleanup shift).

### **Section 1011 - Accidental Discharges; SPCC Plan**

Each User shall provide for protection from accidental or slug discharges of prohibited materials or discharges of materials in volume or concentration exceeding limitations of this Law or of an Industrial Wastewater Discharge

Permit. Users shall immediately notify the Director and DEP of the discharge of wastes in violation of this Law or any Permit. Such discharges may result from:

- (1) Breakdown of pretreatment equipment
- (2) Accidents caused by mechanical failure, or negligence
- (3) Other causes.

Where possible, such immediate notification shall allow the Director and DEP to initiate appropriate countermeasure action at the POTW. The User shall prepare a detailed written statement following any accidental or slug discharge, which describes the causes of the discharge and the measures being taken to prevent future occurrences, within five (5) days of the occurrence, and the Director and DEP shall receive a copy of such report no later than the fifth calendar day following the occurrence. Analytical results and their interpretation may be appended to the report at a date not exceeding 45 calendar days after the occurrence.

When required by the Director or DEP, detailed plans and procedures to prevent accidental or slug discharges shall be submitted to the Director and DEP, and upon review the Director may approve the plan. These plans and procedures shall be called a Spill Prevention, Control, and Countermeasure (SPCC) Plan. The plan shall address, at a minimum, the following:

- (a) Description of discharge practices, including non-routine batch discharges;
- (b) Description of stored chemicals;
- (c) Procedures for immediately notifying the City of Port Jervis and DEP of any accidental or slug discharge. Such notification must also be given for any discharge that would violate any provision of the permit and any National Prohibitive Discharge Standard;
- (d) Procedures to prevent adverse impact from any accidental or slug discharge. Such procedures include, but are not limited to, inspection and maintenance of storage areas, handling and transfer of materials, loading and unloading operations, control of plant site run-off, worker training, building of containment structures or equipment, measures for containing toxic organic pollutants (including solvents), and/or measures and equipment for emergency response.

## **Section 1012 - Posting Notices**

To ensure that the Industrial User's employees are informed of the City of Port Jervis and DEP requirements, a notice shall be posted permanently on appropriate bulletin boards within the User's facility that advise employees of the City and DEP's requirements and whom to call in the event of an accidental discharge in violation of this Law.

### **Section 1013 - Sample Splitting**

When so requested in advance by an Industrial User, and when taking a sample of industrial wastewater, the City of Port Jervis and/or DEP representative(s) shall gather sufficient volume of sample so that the sample can be split into two nearly equal volumes, each of size adequate for the anticipated analytical protocols including any Quality Control (QC) procedures. One of the portions shall be given to the representative of the Industrial User whose wastewater was sampled, and the other portion shall be retained by the City of Port Jervis and/or DEP for their own analysis.

### **Section 1014 - Public Access to Information Maintained by the Director**

When requested, the Director shall make available, to the public, for inspection and/or copying, information and data on industrial users that has been obtained from reports, questionnaires, permit applications, permit and monitoring programs, and inspections, unless the Industrial User specifically requests, and is able to demonstrate to the satisfaction of the Director, that such information, if made public, would divulge processes or methods of production entitled to protection as trade secrets of the user. Wastewater constituents and characteristics, and reports of accidental discharges shall not be recognized as confidential.

Confidential information shall not be made available for inspection and/or copying by the public but shall be disclosed, upon written request, to governmental agencies, for uses related to this Law, or the SPDES Permit, providing that the governmental agency making the request agrees to hold the information confidential, in accordance with State or Federal Laws, Rules and Regulations. The Director shall provide written notice to the Industrial User of any disclosure of confidential information to another governmental agency.

### **Section 1015 A - Access to Property and Records**

The Director and other authorized representatives of the City of Port Jervis, representatives of EPA, NYSDEC, NYSDOH, and/or the Orange County Health Department and DEP, bearing proper credentials and identification, shall be permitted to enter upon all non-residential properties at all times for the purpose of inspection, observation, sampling, flow measurement, and testing

to ascertain a user's compliance with applicable provisions of Federal and State law governing use of the City of Port Jervis POTW, and with the provisions of this Law. Inspections of residential properties shall be performed in proper observance of the resident's civil rights. Such representative(s) shall have the right to set up, on the User's property or property rented/leased by the User, such devices as are necessary to conduct sampling or flow measurement. Guard dogs shall be under proper control of the User while the representatives are on the User's property or property rented/leased by the User. Such representative(s) shall, additionally have access to and may copy any records the User is required to maintain under this Law. Where a User has security measures in force that would require proper identification and clearance before entry into the premises, the User shall make necessary arrangements so that, upon presentation of suitable identification, inspecting personnel will be permitted to enter, without delay, for the purpose of performing their specific responsibilities.

### **Section 1015 B - Access to Easements**

The Director, bearing proper credentials and identification, shall be permitted to enter all private premises through which the City of Port Jervis holds an easement for the purpose of inspection, observation, measurement, sampling, repair, replacement and maintenance of any portion of the City of Port Jervis public sewerage system lying within the easement. All entry and subsequent work on the easement shall be done in accordance with the terms of the easement pertaining to the private premises involved.

### **Section 1015 C - Liability of Property Owner**

During the performance, on private premises, of inspections, sampling, or other similar operations referred to in Sections 1015 A and 1015 B, the inspectors shall observe all applicable safety rules established by the owner or occupant of the premises. The owner and/or occupant shall be held harmless for personal injury or death of the inspector and the loss of or damage to the inspector's supplies and/or equipment; and the inspector shall indemnify the owner and/or occupant against loss or damage to property of the owner or occupant by the inspector and against liability claims asserted against the owner or occupant for personal injury or death of the inspector or for loss of or damage to the inspector's supplies or equipment arising from inspection and sampling operations, except as such may be caused by negligence or failure of the owner or occupant to maintain safe conditions.

### **Section 1016 - Special Agreements**

Nothing in this Article shall be construed as preventing any special agreement or arrangement among the City Of Port Jervis, DEP and any User of the POTW whereby wastewater of unusual strength or character is accepted into the POTW and specially treated, subject to any payments or user charges, as may be applicable. In entering into such a special

agreement, the City of Port Jervis Common Council shall, in consultation with DEP, consider whether the wastewater will:

- (1) pass-through or cause interference
- (2) endanger the public municipal employees
- (3) cause violation of the SPDES Permit
- (4) interfere with any Purpose stated in Section 102
- (5) prevent the equitable compensation to the City of Port Jervis and/or DEP for wastewater conveyance and treatment, and sludge management and disposal

No discharge which violates the Federal Pretreatment Standards will be allowed under the terms of such special agreements.

No agreement shall be entered into without the User having been issued and presently having a permit to discharge wastes into the POTW for treatment and disposal. Additionally the User shall be in compliance with all conditions in the permit and shall not be in arrears in any charges due to the City of Port Jervis before the agreement is entered into. The City of Port Jervis Common Council may condition the agreement.

## **Article 11**

### **Enforcement And Penalties**

Section 1101 –Enforcement Response Plan

Administrative Remedies

- Section 1102 - Notification of Violation
- Section 1103 - Consent Orders
- Section 1104 - Administrative or Compliance Orders
- Section 1105 - Administrative Fines
- Section 1106 - Cease and Desist Orders
- Section 1107 - Termination of Permit
- Section 1108 - Water Supply Severance
- Section 1109 - Show Cause Hearing
- Section 1110 - Failure of User to Petition the Director
- Section 1111 - Notice
- Section 1112 - Right to Choose Multiple Remedies

Judicial Remedies

Section 1113 - Civil Actions for Penalties  
Section 1114 - Court Orders  
Section 1115 - Criminal Penalties  
Section 1116 - Injunctive Relief  
Section 1117 - Summary Abatement

Miscellaneous

Section 1118 - Delinquent Payments  
Section 1119 - Performance Bonds  
Section 1120 - Liability Insurance  
Section 1121 - Informant Rewards

### **Section 1101 – Enforcement Response Plan**

The Director shall prepare an Enforcement Response Plan. The Enforcement Response Plan, in a step-by-step fashion, shall outline the procedures to be followed to identify, document, and respond to violations by Users of the POTW. Such procedures shall be equivalent to procedures described in the document entitled, *Pretreatment Compliance Monitoring and Enforcement Guidance*, USEPA – September, 1986. All violations by Users of the POTW shall be met with some type of enforcement response. The response shall be comprehensive and effective.

The Enforcement Response Plan shall:

- (1) describe how the Director will investigate instances of non-compliance
- (2) describe the types of escalated enforcement actions that the Director will take in response to all anticipated types of User violations and the time periods within which to initiate and follow-up these actions
- (3) adequately reflect the City of Port Jervis Common Council's responsibility to enforce all applicable standards and requirements.

The Enforcement Response Plan shall contain:

- (1) criteria for scheduling periodic inspection and/or sampling visits to POTW Users
- (2) forms and guidelines for documenting compliance data in a manner which will enable the information to be used as evidence
- (3) systems to track due dates, compliance schedule milestones, and pending enforcement actions
- (4) criteria, responsible personnel, and procedures to select and initiate an enforcement action.

The range of appropriate enforcement actions shall be based on the nature and severity of the violation and other relevant factors, such as:

- magnitude of the violation
- duration of the violation
- effect of the violation on the receiving water
- effect of the violation on the POTW
- effect of the violation on the health and safety of the POTW employees
- compliance history of the User
- good faith of the User
- and shall promote consistent and timely use of enforcement remedies.

The City of Port Jervis Common Council shall approve the Enforcement Response Plan. The Enforcement Response Plan shall be reviewed at least every five years.

## **Administrative Remedies**

### **Section 1102 - Notification of Violation**

Whenever the Director finds that any User has violated or is violating this Law, or any Wastewater Discharge Permit, order, prohibition, limitation, or requirement permitted by this Law, the Director may serve upon such person a written Notice of Violation stating the nature of the violation. Within ten (10) calendar days of the date that the Director serves the Notice of Violation, the User shall submit to the Director an explanation of the violation and a plan for the satisfactory correction and future prevention thereof. The correction and prevention plan shall include specific actions. Submission of this plan in no way relieves the User of liability for any violations caused by the User before or after receipt of the Notice of Violation. The Director shall notify DEP of all such violations within 48 hours of issuance of the Notice of Violation.

### **Section 1103 - Consent Orders**

The Director is hereby empowered to enter into Consent Orders, assurances of voluntary compliance, or other similar documents establishing an agreement with the User responsible for the noncompliance. Such orders shall include specific action to be taken by the User to correct the noncompliance within a time period also specified by the order. Consent Orders shall have the same force and effect as an Administrative Order. The Director may consult with the DEP as to the remedial action being ordered prior to the issuance of the Consent Order.

## **Section 1104 - Administrative or Compliance Orders**

When the Director finds that a User has violated or continues to violate this Law or a permit or administrative order issued thereunder, he may issue an Administrative Order to the User responsible for the discharge or violation and directing that, following a specified time period, sewer service shall be discontinued, severed and abated unless the violation is corrected and that there is no reoccurrence of the violation. Administrative Orders may also contain such other requirements as might be reasonably necessary and appropriate to address the noncompliance, including the installation of pretreatment technology, additional self-monitoring, and management practices.

The User may, within fifteen (15) calendar days of the date that the Director serves the Order, petition the Director to modify or suspend the Order. Such petition shall be in written form and shall be transmitted to the Director in accordance with Section 1111. The Director shall then:

- (1) Reject any frivolous petitions,
- (2) Modify or suspend the order, or
- (3) Order the petitioner to show cause in accordance with Section 1109 and may as part of the show cause notice request the User to supply additional information. The User is not relieved of any liability, criminal or civil, for unauthorized discharges or other violations that occur before or after the issuance of the administrative or compliance order or during the petition process.

## **Section 1105 - Administrative Fines**

Notwithstanding any other section of this Law, any User who is found to have violated any provision of this Law, or a wastewater discharge permit or administrative order issued hereunder, shall be fined in an amount not to exceed one thousand dollars (\$1,000.00) per violation. Each day on which noncompliance shall occur or continue shall be deemed a separate and distinct violation.

The User may, within fifteen (15) calendar days of the date that the Director serves the Order instituting a fine, petition the Director to modify or suspend the Order. Such petition shall be in written form and shall be transmitted to the Director in accordance with Section 1111. The Director shall then:

- (1) Reject any frivolous petitions,
- (2) Modify or suspend the fine, or



(3) Order the petitioner to show cause in accordance with Section 1109 and may as part of the show cause notice request the User to supply additional information.

### **Section 1106 - Cease and Desist Orders**

When the Director finds that a User has violated or continues to violate this Law or any permit or administrative order issued hereunder, the Director may issue an administrative order to cease and desist all such violations and direct those persons in noncompliance to:

(1) Comply forthwith

(2) Take such appropriate remedial or preventive action as may be needed to properly address a continuing or threatened violation, including halting operations or terminating the discharge.

The User may, within fifteen (15) calendar days of the date that the Director serves the order, petition the Director to modify or suspend the order. Such petition shall be in written form and shall be transmitted to the Director in accordance with Section 1111. The Director shall then:

(1) Reject any frivolous petitions,

(2) Modify or suspend the order,

(3) Order the petitioner to show cause in accordance with Section 1109 and may as part of the show cause notice request the User to supply additional information.

### **Section 1107 - Termination of Permit**

Any User who violates the following conditions of this Law or a Wastewater Discharge Permit or an administrative order, or any applicable or State and Federal law, is subject to permit termination: (1) Violation of permit conditions or conditions of an administrative order, (2) Failure to accurately report the wastewater constituents and characteristics of its discharge, (3) Failure to report significant changes in operations or wastewater constituents and characteristics, (4) Refusal of reasonable access to the User's premises for the purpose of inspection, monitoring, or sampling, or (5) Failure to pay administrative fines, fees or user charges.

The Director will notify the Non-compliant Industrial User of the proposed termination of the wastewater permit in accordance with Section 1111. The User may, within fifteen (15) calendar days of the date that the Director mails such notification, petition the Director to permit continued use of the

POTW by the user. Such petition shall be in written form and shall be transmitted to the Director in accordance with Section 1111.

The Director shall then:

- (1) Reject any frivolous petitions,
- (2) Order the petitioner to show cause in accordance with Section 1109 and may as part of the show cause notice request the User to supply additional information.

### **Section 1108 - Water Supply Severance**

Whenever a User has violated or continues to violate the provisions of this Law or an order or permit issued hereunder, water service to the User may be severed and service will only recommence, at the User's expense, after it has satisfactorily demonstrated its ability to comply.

The Director will notify the Non-compliant User of the termination of water service in accordance with Section 1111; however, water service can be terminated immediately as an appropriate remedial or preventative action to address a continuing or threatened violation. The User may, within fifteen (15) calendar days of severance, petition the Director to reconnect water supply service. Such petition shall be in written form and shall be transmitted to the Director in accordance with Section 1111. The Director shall then:

- (1) Reject any frivolous petitions,
- (2) Reconnect the water supply, or
- (3) Order the petitioner to show cause in accordance with Section 1109 and may as part of the show cause notice request the User to supply additional information.

### **Section 1109 - Show Cause Hearing**

The Director may order any User who appeals administrative remedies for violations of this Law to show cause, before the City of Port Jervis Common Council, why an enforcement action, initiated by the Director, should not be taken. A notice shall be served on the User specifying the time and place of a hearing to be held by the City Of Port Jervis Common Council regarding the violation, the reasons why the action is to be taken, the proposed enforcement action, and directing the User to show cause before the City of Port Jervis Common Council why the proposed enforcement action should not be taken.

The notice of the hearing shall be served at least ten (10) calendar days before the hearing in accordance with Section 1111 of this Article. Service shall be made on any principal or executive officer of a User's establishment or to any partner in a User's establishment. The City of Port Jervis Common Council itself may conduct the hearing, or it may designate any of its members or any officer, employee or hearing officer of the City Of Port Jervis to conduct the hearing, which may include:

- (1) Issuance, in the name of the City of Port Jervis, notices of hearings, requesting the attendance and testimony of witnesses, and the production of evidence relevant to any matter involved in such hearings,
- (2) The taking of evidence,
- (3) Taking sworn testimony,
- (4) Preparing a report of the evidence and hearing, including transcripts and other evidence, together with recommendations, to the City of Port Jervis Common Council for action thereon.

After the City of Port Jervis Common Council has reviewed the evidence and testimony, it may order the User to comply with the Director's order or fine, modify the Director's order or fine, or vacate the Director's order or fine. Whether or not a duly notified User appears as noticed, immediate enforcement action may be pursued.

### **Section 1110 - Failure of User to Petition the Director**

In the event the Director issues any administrative order, terminates the User's permit, or makes any fine as set forth in this article, and the User fails, within the designated period of time set forth, to petition the Director, as provided in appropriate sections of this article, the User shall be deemed in default and its rights to contest the administrative order or fine shall be deemed waived.

### **Section 1111 - Notice**

The notices, orders, petitions, or other notification that the Director or other City official shall give pursuant to any sections of this Law shall be in writing and shall be served personally or sent by certified mail or registered mail, return receipt requested, postage prepaid. The notice, order, petition, or other communication shall be deemed given upon its personal service or upon mailing as provided herein. Any notice, administrative order, or communication mailed to the User pursuant to this Law shall be mailed to the service address. The Director will use an alternate billing address for mailing to the User, only if the User has provided the alternate address in writing to the Assessor and/or Billing office, prior to the date of the Director's mailing.

Any notice, petition, or other communication to the Director or other City official, shall be in writing and shall be sent by certified or registered mail,

return receipt requested, postage prepared, or shall be served personally. Notices, petitions and other communications to the Director or to other City official or to the DEP shall be deemed given upon actual personal service or upon service of representative(s) so designated to receive service. Otherwise, notices, orders, petitions, or other communication shall be deemed given upon mailing as provided herein.

To the Director:

Director of Public Works  
City Hall, 20 Hammond Street,  
P.O. Box 1002  
Port Jervis, New York 12771

To the Building Official:

Building Official  
Building Department  
City Hall, 20 Hammond Street,  
P.O. Box 1002  
Port Jervis, New York 12771

To the Common Council of the City of Port Jervis:

City Hall, 20 Hammond Street,  
P.O. Box 1002  
Port Jervis, New York 12771

To the DEP:

DEP – Port Jervis Wastewater Treatment Plant  
46 North Maple Avenue  
Port Jervis, New York 12771  
Attention: Chief Operator

### **Section 1112 - Right to Choose Multiple Remedies**

The Director shall have the right, within the Director's sole discretion, to utilize any one or more appropriate administrative remedies set forth in this Article. The Director may utilize more than one administrative remedy established pursuant to this Article, and the Director may hold one show cause hearing that combines more than one enforcement action.

## **Judicial Remedies**

### **Section 1113 - Civil Actions For Penalties**

Any person who violates any of the provisions of or who fails to perform any duty imposed by this Law, or any administrative order or determination of the Director promulgated under this Law, or the terms of any permit issued hereunder, shall be liable to the City of Port Jervis for a civil penalty not to exceed twenty thousand dollars (\$20,000) for each such violation, to be assessed after a hearing (unless the User waives the right to a hearing) held in conformance with the procedures set forth in this Article. Each violation shall be a separate and distinct violation, and in the case of continuing violation, each day's continuance thereof shall be deemed a separate and distinct violation. Such penalty may be recovered in an action brought by the City of Port Jervis attorney, or his designated attorney, at the request of the Director in the name of the City of Port Jervis, in any court of competent jurisdiction giving preference to courts local to the City of Port Jervis. In addition to the above described penalty, the Director may recover all damages incurred by the City of Port Jervis from any persons or Users who violate any provisions of this Law, or who fail to perform any duties imposed by this Law or any administrative order or determination of the Director promulgated under this Law, or the terms of any permit issued hereunder. In addition to the above described damages, the Director may recover all reasonable attorney's fees incurred by the City of Port Jervis in enforcing the provisions of this Article, including reasonable attorney's fees incurred in any action to recover penalties and damages, and the Director may also recover court costs, and other expenses associated with the enforcement activities, including sampling and monitoring expenses.

In determining the amount of civil penalty, the court shall take into account all relative circumstances, including, but not limited to the extent of harm caused by the violation, the magnitude and duration, any economic benefit gained through the User's violation, corrective actions by the User, the compliance history of the User, and any other relative factors as justice may require.

Such civil penalty may be released or compromised by the Director before the matter has been referred to the City of Port Jervis attorney, and where such matter has been referred to the City of Port Jervis attorney, any such penalty may be released or compromised and any action commenced to recover the same may be settled and discontinued by the City of Port Jervis attorney, with the consent of the Director.

### **Section 1114 - Court Orders**

In addition to the power to assess penalties as set forth in this Article, the

Director shall have the power, following the hearing held in conformance with the procedures set forth in this Article, to seek an order:

- (1) Suspending, revoking, or modifying the violator's Wastewater Discharge Permit, or
- (2) Enjoining the violator from continuing the violation.

Any such court order shall be sought in an action brought by the City of Port Jervis attorney, at the request of the Director, in the name of the City of Port Jervis, in any court of competent jurisdiction giving precedence to courts local to the City of Port Jervis.

The City of Port Jervis attorney, at the request of the Director shall petition the Court to impose, assess, and recover such sums imposed according to this Article. In determining amount of liability, the Court shall take into account all relevant circumstances, including, but not limited to, the extent of harm caused by the violation, the magnitude and duration, any economic benefit gained through the User's violation, corrective actions by the User, the compliance history of the User, and any other factor as justice requires.

### **Section 1115 - Criminal Penalties**

Any person who willfully violates any provision of this Law or any final determination or administrative order of the Director made in accordance with this Article shall be guilty of a Class A Misdemeanor, and upon conviction thereof, shall be punished by a fine of not less than Five Hundred Dollars (\$500) nor more than One Thousand Dollars (\$1,000), or imprisonment not to exceed one (1) year or both. Each offense shall be a separate and distinct offense, and, in the case of a continuing offense, each day's continuance thereof shall be deemed a separate and distinct offense.

Any User who knowingly makes any false statements, representations, or certifications in any application, record, report, plan or other document filed or required to be maintained pursuant to this Law, or wastewater permit, or who falsifies, tampers with, or knowingly renders inaccurate any monitoring device or method required under this Law shall be guilty of a Class A Misdemeanor and, upon conviction, shall be punished by a fine of not more than One Thousand Dollars (\$1,000.00) per violation per day or imprisonment for not more than one (1) year or both.

No prosecution, under this Section, shall be instituted until after final disposition of a show cause hearing, if any, was instituted.

### **Section 1116 - Additional Injunctive Relief**

Whenever a User has violated or continues to violate the provisions of this Law or permit or order issued hereunder, the Director, through counsel may petition the Court, in the name of the City of Port Jervis, for the issuance of a preliminary or permanent injunction or both (as may be appropriate) which restrains the violation of, or compels the compliance with any order or determination thereunder by the Director.

### **Section 1117 - Summary Abatement**

Notwithstanding any inconsistent provisions of this Law, whenever the Director finds, after investigation, that any User is causing, engaging in, or maintaining a condition or activity which, in the judgment of the Director, presents an imminent danger to the public health, safety, or welfare, or to the environment, or is likely to result in severe damage to the POTW or the environment, and it therefore appears to be prejudicial to the public interest to allow the condition or activity to go unabated until notice and an opportunity for a hearing can be provided, the Director may, without prior hearing, order such User by notice, in writing wherever practicable or in such other form as practices are intended to be proscribed, to discontinue, abate, or alleviate such condition or activity, and thereupon such person shall immediately discontinue, abate, or alleviate such condition or activity; or where the giving of notice is impracticable, or in the event of a User's failure to comply voluntarily with an emergency order, the Director may take all appropriate action to abate the violating condition. As promptly as possible thereafter, not to exceed fifteen (15) calendar days, the Director shall provide the User an opportunity to be heard, in accordance with the provisions of this Article.

The Director, acting upon the belief that an emergency exists, shall be indemnified against any personal liability that may arise in the performance of his duties to protect the public health, safety, or welfare, or to preserve the POTW or the environment.

### **Miscellaneous**

#### **Section 1118 - Delinquent Payments**

If there shall be any payments which are due to the City of Port Jervis, or any Department thereof, pursuant to any Article or Section of this Law, which shall remain due and unpaid, in whole or in part, for a period of thirty (30) calendar days from the date of billing by the City of Port Jervis, the same shall constitute a default, and there shall be added to the entire amount of the original bill, a penalty equal to five percent (5%) of the original bill.

In the event that there are any sewer fees, assessments, or other service charges which shall have been delinquent for a period of at least sixty (60) calendar days as of December 15 of any year, the City Clerk – Treasurer shall report the names of the defaulting persons to the City of Port Jervis

Mayor, the Director and the Assessor, on or before December 15 of the same year. The City of Port Jervis Clerk is hereby directed to add the entire amount of the sewer fee, assessment, or other service charge which shall be in default, plus penalty and interest, as provided for in this Law, to the real property taxes due and owing to City of Port Jervis in the next succeeding year, and the City of Port Jervis Clerk is directed to collect the same in the same manner as real property taxes due and owing to the City of Port Jervis are collected.

Where charges are delinquent and the violator is not a resident of the City of Port Jervis, or is located outside the geographical boundaries of the City of Port Jervis, then the City of Port Jervis attorney is authorized to seek recovery of charges, including punitive damages, in a court of competent jurisdiction or make arrangements with the appropriate county where the User is located to add the amount of the sewer assessment or other charges which shall be in default, plus penalty and interest, as provided for in the Law, to the real property taxes due to the County in the next ensuing year.

### **Section 1119 - Performance Bonds**

The Director may decline to reissue a permit to any User which has failed to comply with the provisions of this Law or any order or previous permit issued hereunder unless such User first files with it a satisfactory bond, payable to the City of Port Jervis, in a sum not to exceed a value determined by the Director to be necessary to achieve consistent compliance.

### **Section 1120 - Liability Insurance**

The Director may decline to reissue a permit to any User which has failed to comply with the provisions of this Law or any order or previous permit issued hereunder, unless the User first submits proof that it has obtained financial assurances sufficient to restore or repair POTW damage caused by its discharge.

### **Section 1121 - Informant Rewards**

The Director is authorized to pay up to \$500 for information leading to the discovery of noncompliance by a User. In the event that the information provided results in an administrative fine or civil penalty levied against the User, the Director is authorized to disperse up to ten (10) percent of the collected fine or penalty to the informant. However, a single reward payment may not exceed \$10,000, including the discovery reward.

### **Section 1122 - Public Notification**

The Director shall provide public notification, in the daily newspaper with the largest circulation in the City, of Users which were in significant non-compliance of local or Federal pretreatment standards or requirements since



the last such notice. The frequency of such notices shall be at least once per year.

## **Article 12**

### **Charges**

- Section 1201 - Normal Sewage Service Charges
- Section 1202 - Surcharge for Abnormal Sewage
- Section 1203 - Total Sewer Service Charge
- Section 1204 - Segmenting the POTW
- Section 1205 - Measurement of Flow
- Section 1206 - Billing Period
- Section 1207 - Pretreatment Program Costs
- Section 1208 - Reserved
- Section 1209 - Capital Recovery
- Section 1210 - Collection of Charges
- Section 1211 - Fiscal Year for System
- Section 1212 - Impact Fees
- Section 1213 - Use of Revenues
- Section 1214 - Records and Accounts

### **Section 1201 - Normal Sewage Service Charges**

All persons discharging or depositing wastes into the public sewers shall pay a sewer service charge as a flat fee or proportional to the liquid volume of waste so deposited, which charge shall be collected as a sewer rent, as prescribed in the City Fee Schedule and that may be revised from time to time by Resolution of the Port Jervis Common Council pursuant to City of Port Jervis Municipal Code Section 280 – 10. The Common Council may adopt the same or different schedules of rates, fees, charges and surcharges for sewer usage by domestic, non-domestic, commercial and/or industrial users.

### **Section 1202 - Surcharge for Abnormal Sewage**

All persons discharging or depositing wastes with concentrations in excess of the pollutant concentrations in normal sewage shall pay a surcharge, as may be prescribed in the City Fee Schedule.

### **Section 1203 - Total Sewer Service Charge**

The total sewer service charge, (which shall be called the "User Charge"), is comprised of the Normal Sewage Service Charge and any surcharges for Abnormal Sewage, surcharges for Pretreatment Costs and any other

surcharges or fees which may be authorized by Resolution of the Common Council.

#### **Section 1204 - Segmenting the POTWCS**

The service area of the POTWCS may be segmented to assist in a fair distribution of user charges, especially if there is a pump station serving a segment.

#### **Section 1205 - Measurement of Flow**

The volume of flow to be used in computing volume sewer service charges and volume abnormal sewage surcharges shall be based upon metered water consumption as shown on the records of meter readings maintained by the City of Port Jervis Water Department. In the event that a person discharging wastes into the POTWCS produces evidence, to the Director, demonstrating that a substantial portion of the total amount of metered water does not reach the POTWCS, then the Director shall either establish a percentage of the total metered water to be used as a basis for such computations, or direct the installation of appropriate flow measuring (and totalizing) devices to measure and record the actual amount of flow into the POTWCS. In the event that a person discharging wastes into the POTWCS procures all or part of his water supply from un-metered sources, the Director shall either direct the installation of water meters on the other sources of water supply, or direct the installation of appropriate flow measuring devices to measure and record the actual amount of flow into the POTWCS. Any water meters and/or flow measuring devices installed pursuant to this Section shall be of a type and design acceptable to the Director and shall be installed, maintained, and periodically tested as required by the Director, at the owner's expense. All such meters and/or flow measuring devices shall be subject to periodic inspection, testing, and reading by the Director. Any person discharging wastes into the POTWCS may install a flow-measuring device at his option, of the type, design, installation, and maintenance standards of the Director, at the owner's expense.

#### **Section 1206 - Billing Period**

The Billing Period shall be quarterly for industrial and for non-industrial users.

#### **Section 1207 - Pretreatment Program Costs**

The additional charges and fees associated with the operation of the pretreatment program shall be assessed to the User, and include:

- (1) reimbursement of costs of setting up and operating the pretreatment program
- (2) issuing permits

- (3) monitoring, inspections, and surveillance procedures
- (4) costs of equipment and supplies
- (5) reviewing accidental discharge procedures
- (6) construction inspections
- (7) filing appeals
- (8) application for consistent removal status as outlined in 40 CFR 403
- (9) other reasonable expenses to carry out the program to satisfy the requirements of this Law, the NYSDEC, and the Federal government

### **Section 1208 – Reserved**

### **Section 1209 - Capital Recovery**

The City of Port Jervis may institute an equitable procedure for recovering the costs of any capital improvements of those parts of the POTWCS which collect, pump, and convey of wastewaters from those persons discharging such wastewaters into the POTWCS.

### **Section 1210 - Collection of Charges**

Provisions of Article 11 of this Law relating to the collection of penalties shall apply to the collection of Sewer Service Charges and Abnormal Sewage Service Surcharges, unless where otherwise provided by application of the Sewer Use Fee Law of the City of Port Jervis.

### **Section 1211 - Fiscal Year for System**

The POTWCS shall be operated on the basis of a fiscal year commencing on the first day of January and ending on the thirty-first day of December.

### **Section 1212 - Impact Fees**

The City Of Port Jervis Common Council shall have the authority to impose impact fees on new development, which development may:

- (1) - cause enlargement of the service area of the POTW and/or the POTWCS.
- (2) - cause an increase of hydraulic and/or treatment demands on the POTW and/or the POTWCS.

### **Section 1213 - Use of Revenues**

Revenues derived from user charges and associated penalties, and impact fees, shall be credited to a special fund. Monies in this fund shall be used exclusively for the following functions:

- (a) For the payment of the operation and maintenance, including repair and replacement costs of the POTWCS,

- (b) For the discovery and correction of inflow and infiltration,
- (c) For the payment of interest on and the amortization of or payment of indebtedness which has been or shall be incurred for the construction or extension of the POTWCS,
- d) For the extension, enlargement, replacement of, and/or additions to the POTWCS, including any necessary appurtenances.

### **Section 1214 - Records and Accounts**

The City of Port Jervis shall maintain and keep proper books of records and accounts for the POTWCS, separate from all other records and accounts, in which shall be made full and correct entries of all transactions relating to the POTWCS. The City of Port Jervis will cause an annual audit of such books of record and account for the preceding fiscal year to be made by a recognized independent certified public accountant, and will supply such audit report to authorized officials, and the public, on request.

In conjunction with the audit, there shall be an annual review of the sewer charge system to determine if it is adequate to meet expenditures for all programs for the coming year.

Classification of old and new industrial users should also be reviewed annually. The City of Port Jervis shall maintain and carry insurance on all physical properties of the POTWCS, of the kinds and in the amounts normally carried by public utility companies and municipalities engaged in the operation of sewage disposal systems. All moneys received for losses under any such insurance policies shall be applied solely to the replacement and restoration of the property damaged or destroyed.

### **Article 13**

#### **Public Disclosure of POTWCS Operations**

Section 1301- POTWCS Operations Open to the Public

Section 1302- Procedural Requirements Available

Section 1303- Validity through Public Inspection

#### **Section 1301- POTWCS Operations Open to the Public**

It shall be the policy of the City of Port Jervis Common Council to conduct all business with full disclosure to the public.

#### **Section 1302- Procedural Requirements Available**

The nature and requirements of all formal procedures for applying for a permit and for requesting a permit under this Law and for requesting a

hearing shall be formulated by the City of Port Jervis and be made available to any resident of the City of Port Jervis upon request.

### **Section 1303- Validity through Public Inspection**

The City of Port Jervis shall formulate procedures to make available to the public for inspection such orders, statements of policy, and interpretations used by the City of Port Jervis in administration of this Law. No rule, regulation, or civil order shall be valid until it has been available for public inspection.

## **Article 14**

### **Conflicts, Severability, Effective Date And Applicability**

Section 1401- Conflicts

Section 1402- Severability

Section 1403- Effective Date

Section 1404- Applicability

### **Section 1401- Conflicts**

The provisions of any City of Port Jervis law in conflict with any provision of this Law are hereby repealed.

### **Section 1402- Severability**

Each provision of this Law is severable from the others, so that if any provision is held to be illegal or invalid for any reason whatsoever, such illegal or invalid provision shall be severed from this Law that shall nonetheless remain in full force and effect.

### **Section 1403- Effective Date**

This law shall take effect 30 days after its filing in the office of the Secretary of State.

### **Section 1404- Applicability**

Articles 1, 2, 4, 11, 12, 13 and 14 shall apply in all incorporated areas of the City of Port Jervis. Articles 3, 5, 6, 7, 9 and 10 shall apply only in incorporated areas of the City of Port Jervis that are also within the service area of the POTW.

## **Appendix**

## **Parameters of Concern**

Class A - Halogenated Hydrocarbons

Class B - Halogenated Organics (Other than Hydrocarbons)

Class C - Pesticides (Includes Herbicides, Algaecides, Biocides, Slimicides and Mildewcides)

Class D - Aromatic Hydrocarbons

Class E - Tars

Class F - Substituted Aromatics (Other than Hydrocarbons and Non-Halogenated)

Class G - Miscellaneous

Class M - Metals and their Compounds

### **Class A - Halogenated Hydrocarbons**

A01. Methyl Chloride

A02. Methylene Chloride

A03. Chloroform

A04. Carbon Tetrachloride

A05. Freon/Genatron

A06. Other Halomethanes

A07. 1,1,1-Trichloroethane

A08. Other Haloethanes

A09. Vinyl Fluoride

A10. Vinyl Chloride

A11. Dichloroethylene

A12. Trichloroethylene

A13. Tetrachloroethylene

A14. Chlorinated Propane

A15. Chlorinated Propene

A16. Hexachlorobutadiene

A17. Hexachlorocyclopentadiene

A18. Chlorinated Benzene

A19. Chlorinated Toluene

A20. Fluorinated Toluene

A21. Polychlorinated Biphenyl (PCB)

A22. Chlorinated Naphthalene

A23. Dechlorane (C<sub>10</sub>Cl<sub>12</sub>)

A24. Hexachlorocyclohexane (BHC)

A99. Halogenated Hydrocarbons Not Specified Above

### **Class B - Halogenated Organics (Other than Hydrocarbons)**

B01. Phosgene

B02. Methyl Chloromethyl Ether

B03. Bis-Chloromethyl Ether

B04. Other Chloroalkyl Ethers

B05. Benzoyl Chloride

- B06. Chlorothymol
- B07. Chlorinated Phenol
- B08. Chlorinated Cresols or Xylenols
- B09. Chlorendic Acid
- B10. Chloroaryl Ethers
- B11. Dichlorophene or Hexachlorophene
- B12. Chlorinated Aniline (Including Methylene Bis)(2-Chloroaniline)
- B13. Dichlorobenzidine
- B14. Chlorinated Diphenyl Oxide
- B15. Chlorinated Toluidine
- B16. Kepone (C<sub>10</sub>Cl<sub>10</sub>O)
- B17. Dichlorovinyl Sulfonyl Pyridine
- B18. Chloropicrin
- B19. Trichloromethyl Thio-Phthalimide
- B20. Trichloro-Propylsulfonyl Pyridine
- B21. Tetrachloro-Methylsulfonyl Pyridine
- B22. Tetrachloro-Isophthalonitrile

B99. Halogenated Organics Not Specified Above

**Class C - Pesticides (Includes Herbicides, Algaecides, Biocides, Slimicides and Mildewcides)**

- C01. Aldrin/Dieldrin
- C02. Chlordane and Metabolites
- C03. DDT and Metabolites
- C04. Endosulfan/Thiodan and Metabolites
- C05. Endrin and Metabolites
- C06. Heptachlor and Metabolites
- C07. Malathion
- C08. Methoxychlor
- C09. Parathion
- C10. Toxaphene
- C11. Sevin
- C12. Kelthane
- C13. Diazinon
- C14. Dithane
- C15. Carbaryl
- C16. Silvex
- C17. Dithiocarbamates
- C18. Maneb
- C19. Dioxathion
- C20. Tandex/Karbutilate
- C21. Carbofurans
- C22. Pentac
- C23. Folpet
- C24. Dichlone
- C25. Rotenone
- C26. Lindane/Isotox

C27. Simazine  
C28. Methoprene

C99. Pesticides Not Specified Above

**Class D - Aromatic Hydrocarbons**

D01. Benzene  
D02. Toluene  
D03. Xylene  
D04. Biphenyl  
D05. Naphthalene  
D06. Ethylbenzene  
D07. Styrene  
D08. Acenaphthene  
D09. Fluoranthene

D99. Aromatic Hydrocarbons Not Specified Above

**Class E - Tars**

E01. Coal Tar  
E02. Petroleum Tar

E99. Tars Not Specified Above

**Class F - Substituted Aromatics (Other than Hydrocarbons and Non-Halogenated)**

F01. Phenol, Cresol or Xylenol  
F02. Catechol, Resorcinol, or Hydroquinone  
F03. Nitrophenols  
F04. Nitrobenzenes  
F05. Nitrotoluenes  
F06. Aniline  
F07. Toluidines  
F08. Nitroanilines  
F09. Nitroanisole  
F10. Toluene Diisocyanate  
F11. Dimethylaminoazobenzene  
F12. Benzoic Acid (and Benzoate Salts)  
F13. Phthalic, Isophthalic or Terephthalic Acid  
F14. Phthalic Anhydride  
F15. Phthalate Esters  
F16. Phenoxyacetic Acid  
F17. Phenylphenols  
F18. Nitrobiphenyls  
F19. Aminobiphenyls (Including Benzidine)  
F20. Diphenylhydrazine  
F21. Naphthylamines  
F22. Carbazole



F23. Acetylaminofluorene  
F24. Dyes and Organic Pigments  
F25. Pyridine

F99. Substituted Aromatics Not Specified Above

**Class G - Miscellaneous**

G01. Asbestos  
G02. Acrolein  
G03. Acrylonitrile  
G04. Isophorone  
G05. Nitrosamines  
G06. Ethyleneimine  
G07. Propiolactone  
G08. Nitrosodimethylamine  
G09. Dimethylhydrazine  
G10. Maleic Anhydride  
G11. Methyl Isocyanate  
G12. Epoxides  
G13. Nitrofurans  
G14. Cyanide

**Class M - Metals and Their Compounds**

M01. Antimony  
M02. Arsenic  
M03. Beryllium  
M04. Cadmium  
M05. Chromium  
M06. Copper  
M07. Lead  
M08. Mercury  
M09. Nickel  
M10. Selenium  
M11. Silver  
M12. Thallium  
M13. Zinc

M99. Metals Not Specified Above